

Safety data sheet

Page: 1/35

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

n-BUTANOL

Chemical name: Butan-1-ol
INDEX-Number: 603-004-00-6
CAS Number: 71-36-3

REACH registration number: 01-2119484630-38-0000, 01-2119484630-38-0006, 01-2119484630-38-0005, 01-2119484630-38-0004, 01-2119484630-38-0110, 01-2119484630-38-0117, 01-2119484630-38

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY

Contact address:
BASF Ireland DAC
Asgard House, 19-20 City Quay
Dublin, D02 K744
Ireland

Telephone: +353 21 451-7100

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

For products classified as hazardous in accordance with CLP:
National Poisons Information Centre, Beaumont Hospital, Dublin 9
Emergency medical information: 8am-10pm (seven days)
Tel.: 01 8092566

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	H226 Flammable liquid and vapour.
Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Dam. 1	H318 Causes serious eye damage.
STOT SE 3	H336 May cause drowsiness or dizziness.
STOT SE 3	H335 May cause respiratory irritation.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
------	--------------------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

butan-1-ol

Content (W/W): $\geq 99.8\%$
 CAS Number: 71-36-3
 EC-Number: 200-751-6
 INDEX-Number: 603-004-00-6

Flam. Liq. 3
 Acute Tox. 4 (oral)
 Skin Irrit. 2
 Eye Dam. 1
 STOT SE 3 (drowsiness and dizziness)
 STOT SE 3 (irr. to respiratory syst.)
 H226, H318, H315, H302, H336, H335

Regulatory relevant ingredients

butan-1-ol

Content (W/W): $\geq 99.8\%$
 CAS Number: 71-36-3
 EC-Number: 200-751-6
 INDEX-Number: 603-004-00-6

Flam. Liq. 3
 Acute Tox. 4 (oral)
 Skin Irrit. 2
 Eye Dam. 1
 STOT SE 3 (drowsiness and dizziness)
 STOT SE 3 (irr. to respiratory syst.)
 H226, H318, H315, H302, H336, H335

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

71-36-3: butan-1-ol
TWA value 20 ppm (OEL (IE))

PNEC

freshwater: 0.082 mg/l

marine water: 0.0082 mg/l

intermittent release: 2.25 mg/l

STP: 2476 mg/l

sediment (freshwater): 0.324 mg/kg

sediment (marine water): 0.0324 mg/kg

soil: 0.0166 mg/kg

DNEL

worker:

Long-term exposure - systemic and local effects, Inhalation: 310 mg/m³

consumer:

Long-term exposure- systemic effects, Inhalation: 55.357 mg/m³

consumer:

Long-term exposure- systemic effects, oral: 1.5625 mg/kg

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

consumer:

Long-term exposure - local effects, Inhalation: 155 mg/m³

consumer:

Long-term exposure- systemic effects, dermal: 3.125 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid

Form: liquid

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Colour:	colourless	
Odour:	alcohol-like	
Odour threshold:		
	not determined	
Melting point:	< -90 °C	(ASTM D97)
Boiling point:	119 °C (1,013 hPa)	(OECD Guideline 103)
Flammability:	Flammable.	(derived from flash point)
Lower explosion limit:		
	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:		
	For liquids not relevant for classification and labelling.	
Flash point:	35 °C	(ISO 2719, closed cup)
Auto-ignition temperature:	355 °C	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:	4.6 - 5.0 (100 %(m))	
Viscosity, dynamic:	2.947 mPa.s (20 °C)	
Thixotropy:	not thixotropic	
Solubility in water:		(OECD Guideline 105)
	66 g/l (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	1	(OECD Guideline 117)
	(25 °C)	
Vapour pressure:	< 10 hPa (20 °C)	
Relative density:	0.8095 (20 °C)	
Density:	0.8095 g/cm ³ (20 °C)	(ASTM D4052)
	0.7824 g/cm ³ (55 °C)	
Relative vapour density (air):	2.55 (20 °C)	(calculated)
	Heavier than air.	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

Impact sensitivity: Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

Flammable liquids

Sustained combustibility: not determined

Pyrophoric properties

Self-ignition temperature: Temperature: 20 °C Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases: Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil: KOC: 3.471; log KOC: 0.54

(calculated)
(OECD Guideline 115, Ring method)

Surface tension: 69.9 mN/m
(20 °C; 1 g/l)

Molar mass: 74.12 g/mol

SAPT-Temperature: Study scientifically not justified.

Evaporation rate: Value can be approximated from Henry's Law Constant or vapor pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

Vapours may form explosive mixture with air.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Corrosion to metals: No corrosive effect on metal.

Formation of Remarks:

flammable gases:

Forms no flammable gases in the presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with strong oxidizing agents.

10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid:

strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of low toxicity after short-term skin contact. Virtually nontoxic by inhalation. Of low toxicity after single ingestion. The European Union (EU) has classified this substance as 'harmful' after oral exposure.

Experimental/calculated data:

LD50 rat (oral): 2,292 mg/kg (OECD Guideline 401)

The European Union (EU) has classified this substance as 'harmful'.

LC50 rat (by inhalation): > 17.76 mg/l 4 h (OECD Guideline 403)

Highest concentration technically achievable. No mortality was observed. The vapour was tested.

LC50 rat (by inhalation): > 24 mg/l > 8000 ppm 4 h (other)

No mortality was observed. The vapour was tested.

LD50 rabbit (dermal): 3,430 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:

Skin contact causes irritation. Risk of serious damage to eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (BASF-Test)

Serious eye damage/irritation

rabbit: irreversible damage (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: Non-sensitizing. (similar to OECD guideline 429)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

No reliable data was available concerning carcinogenic activity. The chemical structure does not suggest a specific alert for such an effect.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

Experiences in humans

Experimental/calculated data:

High concentrations have a narcotizing effect.

Irritates the respiratory organs.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness). Causes temporary irritation of the respiratory tract.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No substance-specific organotoxicity was observed after repeated administration to animals.

Aspiration hazard

Some authorities consider isobutyl alcohol, n-primary alcohols and ketones with C3-C13 as "May be harmful if swallowed and enters airways"

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 1,376 mg/l, *Pimephales promelas* (OECD 203; ISO 7346; 92/69/EWG, C.1, static)

Aquatic invertebrates:

EC50 (48 h) 1,328 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)

Aquatic plants:

EC50 (96 h) 225 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static)

No observed effect concentration (96 h) 129 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static)

Microorganisms/Effect on activated sludge:

EC10 (17 h) 2,476 mg/l, *Pseudomonas putida* (DIN 38412 Part 8, aerobic)

Chronic toxicity to fish:

No data available.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) 4.1 mg/l, *Daphnia magna* (OECD Guideline 211, semistatic)

Assessment of terrestrial toxicity:

No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Elimination information:

92 % BOD of the ThOD (20 d) (APHA 'Standard Methods', No. 219, 1971) (aerobic, activated sludge, domestic, non-adapted)

Literature data.

Assessment of stability in water:

No data available.

Information on Stability in Water (Hydrolysis):

No data available.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Endocrine disrupting properties

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

12.7. Other adverse effects

The substance is not listed in Regulation (EU) 2024/590 on substances that deplete the ozone layer.

Results of PMT and vPvM assessment

Substance is not included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having PMT/vPvM properties.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:
Disposal must be made according to official regulations.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1120
UN proper shipping name: BUTANOLS

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1120

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

UN proper shipping name: BUTANOLS

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: None known

Inland waterway transport

ADN

UN number or ID number: UN1120
UN proper shipping name: BUTANOLS

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: None known

Transport in inland waterway vessel

UN number or ID number: UN1120
UN proper shipping name: BUTANOLS (n-BUTYLALKOHOL)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Type of inland waterway vessel: N
Cargo tank design: 3
Cargo tank type: 2

Sea transport

IMDG

UN number or ID number: UN 1120
UN proper shipping name: BUTANOLS

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: Marine pollutant: NO
EmS: F-E; S-D

Air transport

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

IATA/ICAO

UN number or ID number: UN 1120
UN proper shipping name: BUTANOLS

Transport hazard class(es): 3
Packing group: III
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code
Product name: n-Butyl alcohol
Pollution category: Z
Ship Type: Not applicable

Further information

To products mentioned in chapter 18 of the IBC-Code, no ship type is assigned within this list.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: P5a

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: P5b

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: P5c

Classification applies for standard conditions of temperature and pressure.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Flam. Liq. 3

Acute Tox. 5 (dermal)

Skin Irrit. 2

STOT SE 3 (irritating to respiratory system)

STOT SE 3 (May cause drowsiness and dizziness.)

Acute Tox. 5 (oral)

Eye Dam. 1

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
Skin Irrit.	Skin irritation
Eye Dam.	Serious eye damage
STOT SE	Specific target organ toxicity — single exposure
H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PMT = Persistent, Mobile and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative. vPvM = very Persistent and very Mobile.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Annex: Exposure Scenarios

Index

1. Formulation

F; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5

2. Distribution of substance

F; ERC2; PROC8a, PROC8b, PROC9

3. Use in laboratories

IS; ERC4; PROC15; PC21

4. Use as a Process chemical

IS; ERC4; PROC1, PROC2, PROC3, PROC4

5. Use in Cleaning Agents

IS; ERC4; PROC7, PROC10, PROC13; PC35

1. Short title of exposure scenario

Formulation

F; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.10a.v1: ESVOC SpERC 4.10a.v1
Operational conditions	
Annual amount used in the EU	213,000,000 kg
Minimum emission days per year	300
Emission factor air	2.5 %
Emission factor water	0.5 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

	by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.065592
	Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
Maximum amount of safe use	1,524.6 t/d
Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	0.0309 mg/m ³
Risk Characterization Ratio (RCR)	0.0001
Assessment method	Qualitative assessment
	Worker - dermal

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	15.442 mg/m ³
Risk Characterization Ratio (RCR)	0.049813
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	30.884 mg/m ³
Risk Characterization Ratio (RCR)	0.099626
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	61.768 mg/m ³
Risk Characterization Ratio (RCR)	0.199252
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	154.42 mg/m ³
Risk Characterization Ratio (RCR)	0.498129
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

2. Short title of exposure scenario

Distribution of substance

F; ERC2; PROC8a, PROC8b, PROC9

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1
Operational conditions	
Annual amount used in the EU	213,000,000 kg
Minimum emission days per year	300
Emission factor air	0.01 %
Emission factor water	0.001 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.005632
	Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
Maximum amount of safe use	252,115.8 kg/d
Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	154.42 mg/m ³
Risk Characterization Ratio (RCR)	0.498129
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	77.21 mg/m ³
Risk Characterization Ratio (RCR)	0.249065
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	154.42 mg/m ³
Risk Characterization Ratio (RCR)	0.498129
Assessment method	Qualitative assessment
	Worker - dermal

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Guidance to Downstream UsersFor scaling see: <http://www.ecetoc.org/tra>

3. Short title of exposure scenario

Use in laboratories

IS; ERC4; PROC15; PC21

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 1.1.v1: ESVOC SpERC 1.1.v1
Operational conditions	
Annual amount used in the EU	213,000,000 kg
Minimum emission days per year	20
Emission factor air	2.5 %
Emission factor water	2 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.005643
	Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
Maximum amount of safe use	17,721.6 kg/d
Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	30.884 mg/m ³
Risk Characterization Ratio (RCR)	0.099626
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

4. Short title of exposure scenario

Use as a Process chemical

IS; ERC4; PROC1, PROC2, PROC3, PROC4

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.1o.v2
Operational conditions	
Annual amount used in the EU	213,000,000 kg
Minimum emission days per year	300
Emission factor air	1 %
Emission factor water	1 %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.55
	Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
Maximum amount of safe use	1,290.9 t/d
Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

	Worker - inhalation, long-term - local
Exposure estimate	0.0309 mg/m ³
Risk Characterization Ratio (RCR)	0.0001
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	15.442 mg/m ³
Risk Characterization Ratio (RCR)	0.049813
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

	Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	30.884 mg/m ³
Risk Characterization Ratio (RCR)	0.099626
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	61.768 mg/m ³
Risk Characterization Ratio (RCR)	0.199252
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

5. Short title of exposure scenario

Use in Cleaning Agents

IS; ERC4; PROC7, PROC10, PROC13; PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.6a.v1: ESVOC SpERC 4.6a.v1
Operational conditions	
Annual amount used in the EU	213,000,000 kg
Minimum emission days per year	20
Emission factor air	30 %
Emission factor water	0.01 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts,

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

	Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.006714
	Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
Maximum amount of safe use	744,715.4 kg/d
Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Risk Management Measures	
Ensure minimization of manual phases Clean equipment and the work area every day. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Ensure that a spraying booth is used.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - local
Exposure estimate	0.0001 mg/m ³
Risk Characterization Ratio (RCR)	0.000001
Assessment method	Qualitative assessment
	Worker - dermal

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	154.42 mg/m ³
Risk Characterization Ratio (RCR)	0.498129
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	butan-1-ol Content: >= 0 % - <= 100 %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 02.01.2026

Version: 7.0

Date / Previous version: 31.10.2025

Previous version: 6.0

Product: **n-BUTANOL**

(ID no. 30034729/SDS_GEN_IE/EN)

Date of print 11.06.2026

Physical state	liquid
Vapour pressure of the substance during use	1000 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Ensure minimization of manual phases Avoid frequent and direct contact with substance. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid splashing.	
Wear suitable working clothes.	
Use suitable eye protection.	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, ECETOC TRA v3.1, Worker
	Worker - inhalation, long-term - local
Exposure estimate	154.42 mg/m ³
Risk Characterization Ratio (RCR)	0.498129
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
