

Safety data sheet

Page: 1/58

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ISOTRIDECANOL N

Chemical name: Tridecanol N

CAS Number: 27458-92-0

REACH registration number: 01-2119488528-21-0000, 01-2119488528-21-0008

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: process chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Contact address:

BASF plc

4th and 5th Floors, 2 Stockport Exchange

Railway Road, Stockport, SK1 3GG

UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Skin Corr./Irrit. 2	H315 Causes skin irritation.
Aquatic Acute 1	H400 Very toxic to aquatic life.
Aquatic Chronic 1	H410 Very toxic to aquatic life with long lasting effects.

M-factor acute: 1
M-factor chronic: 1

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Warning

Hazard Statement:

H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273	Avoid release to the environment.
P280	Wear protective gloves.

Precautionary Statements (Response):

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P391	Collect spillage.
P332 + P313	If skin irritation occurs: Get medical attention.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: Isotridecan-1-ol

2.3. Other hazards

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

Isotridecan-1-ol

CAS Number: 27458-92-0

EC-Number: 248-469-2

Hazardous ingredients (GHS)

Isotridecan-1-ol

Content (W/W): $\geq 99.8\%$ - $\leq 100\%$

CAS Number: 27458-92-0

EC-Number: 248-469-2

Skin Corr./Irrit. 2

Aquatic Acute 1

Aquatic Chronic 1

M-factor acute: 1

M-factor chronic: 1

H315, H400, H410

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: The product is combustible. Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

No special precautions necessary. Substance/product is non-flammable.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

PNEC

| freshwater: 0.00052 mg/l

| marine water: 0.000052 mg/l

| intermittent release: 0.00297 mg/l

| sediment (freshwater): 4.95 mg/kg

sediment (marine water): 0.495 mg/kg

soil: 0.314 mg/kg

STP: 10 mg/l

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 26.5 mg/m³

worker:

Long- and short-term exposure - local effects, Inhalation: 164 mg/m³

worker:

Long-term exposure- systemic effects, dermal: 7.5 mg/kg

consumer:

Long-term exposure- systemic effects, Inhalation: 7.5 mg/m³

consumer:

Long-term exposure- systemic effects, dermal: 3.75 mg/kg

consumer:

Long-term exposure- systemic effects, oral: 1.9 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	slightly viscous, oily	
Colour:	colourless, clear	
Odour:	almost odourless	
Odour threshold:	not determined	
pH value:	not applicable	
Melting point:	-78 °C	(DTA)
Boiling point:	260.8 °C (1,013 hPa)	(other)
Flash point:	128 °C	(ISO 2719)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Ignition temperature:	230 °C	(DIN 51794)
Vapour pressure:	< 0.01 hPa (20 °C) 0.022 hPa (50 °C)	
Density:	0.8426 g/cm ³ (20 °C)	(OECD Guideline 109)
Relative density:	0.8426 (20 °C)	
Relative vapour density (air):	6.9 (20 °C) Heavier than air.	(calculated)
Solubility in water:	2 mg/l (20 °C, pH 6.6 - 7.6)	(OECD Guideline 105)
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	6.1 (23 °C)	(OECD Guideline 117)
Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	34.9 mPa.s (20 °C)	(calculated (from kinematic viscosity))
Viscosity, kinematic:	42.9 mm ² /s (20 °C) 41.4 mm ² /s (20 °C)	(DIN 51562) (OECD Guideline 114)
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	

9.2. Other information

Self heating ability:	not applicable, the product is a liquid	
SADT:	Study scientifically not justified. Not a substance/mixture liable to self-decomposition according to GHS.	
pKA:	not applicable	
Adsorption/water - soil:	KOC: 1122; log KOC: 3.05	(OECD Guideline 121)
Surface tension:	64.24 mN/m (20 °C; 0.0029 g/l)	(OECD Guideline 115, Ring method)
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.	
Molar mass:	200.36 g/mol	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Formation of flammable gases: Remarks: Forms no flammable gases in the presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid:
strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data:

LD50 rat (oral): > 2,000 mg/kg (OECD Guideline 423)

LC0 rat (by inhalation): 0.006 mg/l 8 h (IRT)

No mortality within the stated exposition time as shown in animal studies. The vapour was tested.

LD50 rabbit (dermal): approx. 6,000 mg/kg (similar to OECD guideline 402)

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Irritation

Assessment of irritating effects:

Skin contact causes irritation. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation

rabbit: non-irritant (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Intracutaneous test guinea pig: Non-sensitizing.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

No mutagenic effect was found in various tests with bacteria and mammalian cell culture. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

No data available concerning carcinogenic effects. The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The results were determined in a Screening test.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies. Mortality observed in rabbits following high oral exposure.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Aspiration hazard

not applicable

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

Very toxic (acute effect) to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Very toxic to aquatic organisms based on long-term (chronic) toxicity study data.

Toxicity to fish:

LC50 (96 h) 0.55 mg/l, *Brachydanio rerio* (OECD Guideline 203, semistatic)

The statement of the toxic effect relates to the analytically determined concentration. The product has low solubility in the test medium. An aqueous solution prepared with solubilizers has been tested.

Aquatic invertebrates:

EC50 (48 h) 0.391 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)

The statement of the toxic effect relates to the analytically determined concentration. The product has low solubility in the test medium. An eluate has been tested.

Aquatic plants:

EC50 (72 h) 0.297 mg/l (growth rate), *Desmodesmus subspicatus* (OECD Guideline 201, static)

The statement of the toxic effect relates to the analytically determined concentration. The product has low solubility in the test medium. An eluate has been tested.

EC10 (72 h) 0.215 mg/l (growth rate), *Desmodesmus subspicatus* (OECD Guideline 201, static)

The statement of the toxic effect relates to the analytically determined concentration. The product has low solubility in the test medium. An eluate has been tested.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Microorganisms/Effect on activated sludge:

EC20 (0.5 h) > 1,000 mg/l, activated sludge, domestic (DIN EN ISO 8192, aerobic)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

No observed effect concentration 0.00523 mg/l, Fish (calculated)

Chronic toxicity to aquatic invertebrates:

No observed effect concentration 0.00793 mg/l, Daphnia sp. (calculated)

EC10 (28 d) 495 mg/kg dw, Chironomus riparius (OECD Guideline 218, static)

Assessment of terrestrial toxicity:

Toxic effects have been observed in studies with soil living organisms. Toxic effects have been observed in studies with terrestrial plants.

Soil living organisms:

EC10 (28 d) 1,000 mg/kg, soil dwelling microorganisms (OECD Guideline 216, natural soil)

LC50 (14 d) 64.5 mg/kg, Eisenia foetida (OECD Guideline 207, artificial soil)

Terrestrial plants:

No observed effect concentration (22 d) 15.7 mg/kg, Brassica napus (OECD Guideline 208)

Other terrestrial non-mammals:

No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Elimination information:

90 - 100 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis):

No data available.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

Bioaccumulation potential:

Bioconcentration factor (BCF): < 285, Fish (calculated)

The product has not been tested. The statement has been derived from the structure of the product.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN3082

UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Transport hazard class(es): N.O.S. (contains ISOTRIDECAN-1-OL)
 9, EHS
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

RID

UN number or ID number: UN3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S. (contains ISOTRIDECAN-1-OL)
 Transport hazard class(es): 9, EHS
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

Inland waterway transport**ADN**

UN number or ID number: UN3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S. (contains ISOTRIDECAN-1-OL)
 Transport hazard class(es): 9, EHS
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

Transport in inland waterway vessel

UN number or ID number: UN3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S. (contains ISOTRIDECAN-1-OL)
 Transport hazard class(es): 9, N1, F
 Packing group: III
 Environmental hazards: yes
 Type of inland waterway vessel: N
 Cargo tank design: 2
 Cargo tank type: 3

Sea transport**IMDG**

UN number or ID number: UN 3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Transport hazard class(es): N.O.S. (contains ISOTRIDECAN-1-OL)
 9, EHSM
 Packing group: III
 Environmental hazards: yes
 Marine pollutant: YES
 Special precautions for user:

Air transport

IATA/ICAO

UN number or ID number: UN 3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S. (contains ISOTRIDECAN-1-OL)
 Transport hazard class(es): 9, EHSM
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Product name: Alcohols (C13+)
Pollution category: Y
Ship Type: 2

Further information

This product is subject to the most recent edition of "The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations" and their amendments (United Kingdom).

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

UK REACH SI, Annex XVII, Marketing and Use Restrictions

Number on List: 3

Concentration limit: 0.1 %

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: E1

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

This product may be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments if specific threshold tonnages are exceeded (United Kingdom).

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Aquatic Acute 1
 Aquatic Chronic 1
 Skin Corr./Irrit. 2

M-factor acute: 1
 M-factor chronic: 1

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
Aquatic Acute	Hazardous to the aquatic environment - acute
Aquatic Chronic	Hazardous to the aquatic environment - chronic
H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Annex: Exposure Scenarios

Index

1. Formulation & (re)packing of substances and mixtures, (use in professional settings), (use in industrial settings)

ERC2; PROC3, PROC5, PROC19

2. Use in packaging, (use in industrial settings), (use in professional settings)

ERC2; PROC8a, PROC8b, PROC9

3. Use as an intermediate, (use in industrial settings)

ERC6a; PROC2, PROC3, PROC4

4. Use as laboratory reagent/agent, (use in industrial settings), (use in professional settings)

ERC2; PROC15

5. Use as processing aid, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4

6. Use in Cleaning Agents, (use in industrial settings)

ERC4; PROC7, PROC10, PROC13

7. Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC4, PC9a, PC35

8. Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC10, PROC11, PROC13

9. Use in Coatings, (use in industrial settings)

ERC4; PROC7, PROC10, PROC13

10. Use in Coatings, (consumer use)

ERC8a, ERC8d; PC1, PC9a, PC15, PC18, PC23, PC26, PC34

11. Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC10, PROC11, PROC13

1. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (use in professional settings), (use in industrial settings)

ERC2; PROC3, PROC5, PROC19

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.10a.v1: ESVOC SpERC 4.10a.v1

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Operational conditions	
Annual amount used in the EU	440,000 kg
Minimum emission days per year	300
Emission factor air	0.25 %
Emission factor water	0.002 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.381093
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	3,848.6 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.018286
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, Workplace measurements
	Worker - dermal, long-term - systemic
Exposure estimate	4 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.533333
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1.2616 mg/m ³
Risk Characterization Ratio (RCR)	0.047607
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

2. Short title of exposure scenario

Use in packaging, (use in industrial settings), (use in professional settings)

ERC2; PROC8a, PROC8b, PROC9

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	Emissions to the environment from distribution activities are covered by the exposure assessments of the respective life cycle stages. Consequently, no environmental exposure estimation and risk characterisation is provided for this scenario.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.182857

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

3. Short title of exposure scenario

Use as an intermediate, (use in industrial settings)

ERC6a; PROC2, PROC3, PROC4

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 7.12a.v1: ESVOC SpERC 7.12a.v1
Operational conditions	
Annual amount used in the EU	290,000 kg
Minimum emission days per year	300
Emission factor air	0 %
Emission factor water	0.003 %
Emission factor soil	0.1 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.377157
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	2,563 kg/d

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk from environmental exposure is driven by marine water.

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.036571
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	8.3484 mg/m ³
Risk Characterization Ratio (RCR)	0.315033
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0.078 Pa

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

during use	
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.018286
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.182857
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

* * * * *

4. Short title of exposure scenario

Use as laboratory reagent/agent, (use in industrial settings), (use in professional settings)
ERC2; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 1.1.v1: ESVOC SpERC 1.1.v1
Operational conditions	
Annual amount used in the EU	20 kg
Minimum emission days per year	20
Emission factor air	2.5 %
Emission factor water	2 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.270898
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	3.7 kg/d

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk from environmental exposure is driven by marine water.

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker Worker - dermal, long-term - systemic
Exposure estimate	0.0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.009143
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

5. Short title of exposure scenario

Use as processing aid, (use in industrial settings)
ERC4; PROC1, PROC2, PROC3, PROC4

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.18.v1: ESVOC SpERC 2.18.v1
Operational conditions	
Annual amount used in the EU	290,000 kg
Minimum emission days per year	300

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDEKANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Emission factor air	1 ppm
Emission factor water	0.003 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures

Air treatment measures considered suitable are, e.g.	Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d

Exposure estimate and reference to its source

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.377157
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	2,563 kg/d

Risk from environmental exposure is driven by marine water.

Contributing exposure scenario

Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
--------------------------------	--

Operational conditions

Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Exposure estimate and reference to its source

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.004571

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.0835 mg/m ³
Risk Characterization Ratio (RCR)	0.00315
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.036571
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	8.3484 mg/m ³
Risk Characterization Ratio (RCR)	0.315033
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Concentration of the substance	Isotridecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.009143
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.182857
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

6. Short title of exposure scenario

Use in Cleaning Agents, (use in industrial settings)

ERC4; PROC7, PROC10, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.6a.v1: ESVOC SpERC 4.6a.v1
Operational conditions	
Annual amount used in the EU	120,000 kg
Minimum emission days per year	20
Emission factor air	30 %
Emission factor water	0.3 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.052476
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	95,282.2 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 0.3 l/min
Risk Management Measures	
Wear chemically resistant gloves in combination with specific activity training	Effectiveness: 95 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker Worker - dermal, long-term - systemic
Exposure estimate	2.1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.285714
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5 Worker - inhalation, long-term - systemic
Exposure estimate	15 mg/m ³

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk Characterization Ratio (RCR)	0.566038
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

7. Short title of exposure scenario

Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC4, PC9a, PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.042853
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.639339 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.042853
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.639339 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PC4: Anti-Freeze and De-icing products.
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	100 uses per year
Room size	15 m ³
Ventilation rate per hour	2.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24.6 sec
Contact rate	46 mg/min
Release duration	0.41 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0079 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.00212
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0103 mg/m ³
Risk Characterization Ratio (RCR)	0.001375
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Room size	20 m3
Ventilation rate per hour	0.6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0.5 g Relevant for dermal exposure estimates
Release area	20000 cm ²
	Release area increases over time
Release duration	60 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0021 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000562
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.1651 mg/m ³
Risk Characterization Ratio (RCR)	0.022019
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 0.13 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	58 m3
Ventilation rate per hour	0.5
Temperature (Application)	20 °C
body weight	65 kg

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Uptake fraction dermal	100 %
	Amount per use 19 g Relevant for dermal exposure estimates
Release area	100000 cm ²
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.1083 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.028873
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0001 mg/m ³
Risk Characterization Ratio (RCR)	0.000017
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
Room size	15 m ³
Ventilation rate per hour	2.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24.6 sec
Contact rate	46 mg/min
Release duration	0.41 min
	Relevant for dermal exposure estimates

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.029 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.007737
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0103 mg/m ³
Risk Characterization Ratio (RCR)	0.001375
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

8. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC10, PROC11, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m ³ /d)	2,000 m ³ /d

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.036383
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.37651 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.036383
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.37651 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 50 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 0.3 l/min
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

in place	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, Workplace measurements
	Worker - dermal, long-term - systemic
Exposure estimate	3.9 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.52
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	5.4 mg/m ³
Risk Characterization Ratio (RCR)	0.203774

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

9. Short title of exposure scenario

Use in Coatings, (use in industrial settings)
ERC4; PROC7, PROC10, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1
Operational conditions	
Annual amount used in the EU	120,000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	0.007 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.365351
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	1,094.8 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 0.3 l/min
Risk Management Measures	
Wear chemically resistant gloves in combination with specific activity training	Effectiveness: 95 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.285714
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	15 mg/m ³
Risk Characterization Ratio (RCR)	0.566038
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

10. Short title of exposure scenario

Use in Coatings, (consumer use)

ERC8a, ERC8d; PC1, PC9a, PC15, PC18, PC23, PC26, PC34

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.042853
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.639339 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	95 %

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.042853
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.639339 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PC1: Adhesives, Sealants
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year
Room size	58 m3
Ventilation rate per hour	0.5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	40000 cm ²
	Release area is constant
Release duration	75 min
	Relevant for inhalative exposure estimates

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Contact rate	30 mg/min
Release duration	75 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0024 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000632
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.252 mg/m ³
Risk Characterization Ratio (RCR)	0.033602
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year
Room size	20 m ³
Ventilation rate per hour	0.6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm ²
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0152 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.004046
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0836 mg/m ³
Risk Characterization Ratio (RCR)	0.01115
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC15: Non-metal-surface treatment products.
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year
Room size	20 m ³
Ventilation rate per hour	0.6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm ²
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0152 mg/kg bw/day

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk Characterization Ratio (RCR)	0.004046
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0836 mg/m ³
Risk Characterization Ratio (RCR)	0.01115
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC18: Ink and Toners.
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 2 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	2 uses per day
Room size	34 m ³
Ventilation rate per hour	1.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	60 sec
Contact rate	30 mg/min
Release duration	2 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.1846 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.049231
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0006 mg/m ³
Risk Characterization Ratio (RCR)	0.000078
	The exposure calculation is based on the mean

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC23: Leather tanning, dye, finishing, impregnation and care products.
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year
Room size	58 m3
Ventilation rate per hour	0.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	180 sec
Contact rate	100 mg/min
Release duration	3 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0013 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000337
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.447 mg/m ³
Risk Characterization Ratio (RCR)	0.0596
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC26: Paper and Board dye, finishing and impregnation products: including bleaches and other processing aids

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: $\geq 0\%$ - $\leq 10\%$
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	Exposure duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	2 uses per year
Room size	34 m ³
Ventilation rate per hour	1.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	900 sec
Contact rate	100 mg/min
Release duration	15 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0126 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.003372
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	1.9789 mg/m ³
Risk Characterization Ratio (RCR)	0.263857
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	
Contributing exposure scenario	
Use descriptors covered	PC34: Textile dyes, finishing and impregnating products: including bleaches and other processing aids
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: $\geq 0\%$ - $\leq 10\%$
Vapour pressure of the substance during use	0.078 Pa

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Duration and Frequency of activity	Exposure duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	2 uses per year
Room size	34 m ³
Ventilation rate per hour	1.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	900 sec
Contact rate	100 mg/min
Release duration	15 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0126 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.003372
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	1.9789 mg/m ³
Risk Characterization Ratio (RCR)	0.263857
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC34: Textile dyes, finishing and impregnating products: including bleaches and other processing aids
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Skin contact factor	80 %
Uptake fraction dermal	100 %

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Leachable fraction	1 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: migration, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	1.2308 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.328205
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

11. Short title of exposure scenario

Use in Coatings, (use in professional settings)
ERC8a, ERC8d; PROC10, PROC11, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.036383
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.37651 kg/d

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Risk from environmental exposure is driven by marine water.

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.036383
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	0.37651 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 50 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 0.3 l/min
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, Workplace measurements

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 15.03.2024

Version: 13.0

Date / Previous version: 01.10.2023

Previous version: 12.0

Product: **ISOTRIDECANOL N**

(ID no. 30034826/SDS_GEN_GB/EN)

Date of print 31.05.2024

	Worker - dermal, long-term - systemic
Exposure estimate	3.9 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.52
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	5.4 mg/m ³
Risk Characterization Ratio (RCR)	0.203774

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	Isotridecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.078 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.365714
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.308 mg/m ³
Risk Characterization Ratio (RCR)	0.238037
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
