

Safety data sheet

Page: 1/16

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

1. Identification

Product identifier

DIMETHYLAMINOETHYL ACRYLATE

Chemical name: 2-(Dimethylamino)ethyl acrylate

CAS Number: 2439-35-2

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monomer.

Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Telephone: +49 621 60-0

E-mail address: global.info@basf.com

Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Flam. Liq. 3

Acute Tox. 1 (Inhalation - vapour)

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

Acute Tox. 4 (oral)
Acute Tox. 3 (dermal)
Skin Corr./Irrit. 1B
Eye Dam./Irrit. 1
Skin Sens. 1
Aquatic Acute 1
Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H311	Toxic in contact with skin.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H412	Harmful to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe dust/mist/vapours.
P273	Avoid release to the environment.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P284	In case of inadequate ventilation wear respiratory protection.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P391	Collect spillage.
P370 + P378	In case of fire: Use ... to extinguish.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

3. Composition/Information on Ingredients

Substances

Chemical nature

2-(Dimethylamino)ethyl acrylate
 CAS Number: 2439-35-2
 EC-Number: 219-460-0

Hazardous ingredients (GHS)

According to UN GHS criteria

2-(Dimethylamino)ethyl acrylate

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

<p>Content (W/W): >= 99 % - <= 100 % CAS Number: 2439-35-2 EC-Number: 219-460-0</p>	<p>Flam. Liq. 3 Acute Tox. 1 (Inhalation - vapour) Acute Tox. 4 (oral) Acute Tox. 3 (dermal) Skin Corr./Irrit. 1B Eye Dam./Irrit. 1 Skin Sens. 1 Aquatic Acute 1 Aquatic Chronic 3 H226, H311, H330, H302, H317, H314, H412, H400</p>
---	--

Mequinol

<p>Content (W/W): >= 0,07 % - <= 0,295 % CAS Number: 150-76-5 EC-Number: 205-769-8 INDEX-Number: 604-044-00-7</p>	<p>Acute Tox. 4 (oral) Skin Corr./Irrit. 3 Skin Sens. 1 Aquatic Acute 2 Aquatic Chronic 3 H316, H302, H317, H412, H401</p>
--	---

2-Dimethylaminoethanol

<p>Content (W/W): >= 0 % - <= 0,1 % CAS Number: 108-01-0 EC-Number: 203-542-8 INDEX-Number: 603-047-00-0</p>	<p>Flam. Liq. 3 Acute Tox. 3 (Inhalation - vapour) Acute Tox. 4 (oral) Acute Tox. 4 (dermal) Skin Corr./Irrit. 1B Eye Dam./Irrit. 1 STOT SE 3 (irr. to respiratory syst.) Aquatic Acute 3 H226, H331, H335, H314, H302 + H312, H402</p>
---	---

Specific concentration limit:

STOT SE 3, irr. to respiratory syst.: >= 5 %

For the classifications not written out in full in this section the full text can be found in section 16.

Mixtures

Not applicable

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Do not induce vomiting. Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

The product is combustible. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools. Avoid contact with the skin, eyes and clothing.

Take off immediately all contaminated clothing.

Environmental precautions

Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water.

Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

7. Handling and Storage

Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 25 °C

Storage duration: 6 Months

Storage temperature: 40 °C

Storage duration: 0,5 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

It is recommended to keep a safe distance of +2 degrees above the crystallization range.

The product is stabilized, the shelf life should be noted.

Storage temperature: 45 °C

A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.

Storage temperature: 60 °C

All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

108-01-0: 2-Dimethylaminoethanol

150-76-5: Mequinol

Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid inhalation of vapour. Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form:	liquid
Colour:	yellowish
Odour:	amine-like
Odour threshold:	not determined
pH value:	10,0 (143 g/l, 20 °C)

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

Melting point:	< -61 °C Literature data.	
Boiling point:	172,8 °C (1.013,25 hPa) Extrapolated value	(measured)
Flash point:	58 °C	(DIN 51755, closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability:	Flammable.	
Lower explosion limit:	0,6 %(V) (45 °C)	
Upper explosion limit:	For liquids not relevant for classification and labelling. 5,5 %(V) (88 °C)	
Ignition temperature:	195 °C	(DIN 51794)
Vapour pressure:	1 hPa (19,1 °C) dynamic 8 hPa (50 °C)	(measured)
Density:	0,938 g/cm ³ (20 °C) Literature data. 0,9124 g/cm ³ (50 °C)	(OECD Guideline 109)
Relative density:	0,938 (20 °C) Literature data.	
Relative vapour density (air):	4,93 (20 °C)	(calculated)
Solubility in water:	Heavier than air. hydrolyzes 240 g/l (20 °C)	(calculated)
Solubility (qualitative) solvent(s):	organic solvents miscible	
Partitioning coefficient n-octanol/water (log Kow):	0,68 (25 °C)	(OECD Guideline 107)
Self ignition:	not self-igniting	Test type: Spontaneous self-ignition at room-temperature.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	1,34 mPa.s (20 °C) 0,96 mPa.s (40 °C)	(calculated (from kinematic viscosity)) (calculated (from kinematic viscosity))
Viscosity, kinematic:	1,43 mm ² /s (20 °C)	(OECD 114)

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

1,04 mm²/s
(40 °C)

(OECD 114)

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

Other information

Self heating ability: Not tested on account of the low melting-point.

It is not a substance capable of spontaneous heating.

SADT: Not a substance/mixture liable to self-decomposition according to GHS.

pKA: not applicable

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Grain size distribution: The substance / product is marketed or used in a non solid or granular form.

Molar mass: 143,19 g/mol

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: Corrosive effects to metal are not anticipated.

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.
-------------------------------	----------	--

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

Incompatible materials

Substances to avoid:

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts
Inert gas

Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of very high toxicity after short-term inhalation. Of pronounced toxicity after short-term skin contact.

Experimental/calculated data:

LD50 rat (oral): > 455 mg/kg (OECD Guideline 401)

LC50 rat (by inhalation): 0,22 mg/l 4 h (BASF-Test)

LD50 rat (dermal): 419 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:

Corrosive! Damages skin and eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Corrosive. (OECD Guideline 404)

Serious eye damage/irritation rabbit: irreversible damage (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:

Caused skin sensitization in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: skin sensitizing (OECD Guideline 406)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was mutagenic in various cell culture test systems; however, these results could not be confirmed in tests with mammals.

Carcinogenicity

Assessment of carcinogenicity:

Study does not need to be conducted.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

After repeated administration the prominent effect is the induction of corrosion.

Aspiration hazard

not applicable

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

Very toxic (acute effect) to aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 8,49 mg/l, *Oryzias latipes* (OECD 203; ISO 7346; 84/449/EEC, C.1, semistatic)

Aquatic invertebrates:

EC50 (48 h) 9,92 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, semistatic)

Aquatic plants:

EC50 (72 h) 0,88 mg/l (growth rate), *Selenastrum capricornutum* (Guideline 92/69/EEC, C.3, static)

The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge:

EC20 (0,5 h) > 1.000 mg/l, activated sludge (other)

Chronic toxicity to fish:

Study scientifically not justified.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) 3 mg/l, *Daphnia magna* (OECD Guideline 211, semistatic)

Assessment of terrestrial toxicity:

Study scientifically not justified.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Elimination information:

96 % (28 d) (OECD 301 A (old version)) (aerobic, municipal sewage treatment plant effluent)

> 95 % (28 d) (OECD 302B; ISO 9888; 88/302/EEC, part C) (aerobic, activated sludge)

Assessment of stability in water:

In contact with water the substance will hydrolyse rapidly.

Bioaccumulative potential

Assessment bioaccumulation potential:

No significant accumulation in organisms is expected as a result of the distribution coefficient of n-octanol/water (log Pow).

Bioaccumulation potential:

Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Results of PBT and vPvB assessment

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control.

13. Disposal Considerations

Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:

Uncleaned empties should be disposed of in the same manner as the contents.

14. Transport Information

Land transport

ADR

UN number or ID number: UN3302

UN proper shipping name: 2-DIMETHYLAMINOETHYL ACRYLATE STABILIZED

Transport hazard class(es): 6.1, EHSM

Packing group: II

Environmental hazards: yes

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN3302

UN proper shipping name: 2-DIMETHYLAMINOETHYL ACRYLATE STABILIZED

Transport hazard class(es): 6.1, EHSM

Packing group: II

Environmental hazards: yes

Special precautions for user: None known

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.09.2023

Version: 4.0

Product: **DIMETHYLAMINOETHYL ACRYLATE**

(ID no. 30041959/SDS_GEN_00/EN)

Date of print 07.06.2024

Inland waterway transport

ADN

UN number or ID number: UN3302

UN proper shipping name: 2-DIMETHYLAMINOETHYL ACRYLATE STABILIZED

Transport hazard class(es): 6.1, EHSM

Packing group: II

Environmental hazards: yes

Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 3302

UN proper shipping name: 2-DIMETHYLAMINOETHYL ACRYLATE STABILIZED

Transport hazard class(es): 6.1, EHSM

Packing group: II

Environmental hazards: yes

Special precautions for user: Marine pollutant: YES

EmS: F-A; S-A

Air transport

IATA/ICAO

UN number or ID number: UN 3302

UN proper shipping name: 2-DIMETHYLAMINOETHYL ACRYLATE STABILIZED

Transport hazard class(es): 6.1

Packing group: II

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: None known

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use. Any other intended applications should be discussed with the manufacturer.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Sens.	Skin sensitization
Aquatic Acute	Hazardous to the aquatic environment - acute
Aquatic Chronic	Hazardous to the aquatic environment - chronic
STOT SE	Specific target organ toxicity — single exposure
H226	Flammable liquid and vapour.
H311	Toxic in contact with skin.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H412	Harmful to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.
H316	Causes mild skin irritation.
H401	Toxic to aquatic life.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H402	Harmful to aquatic life.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.