

Revision date : 2024/07/24 Version: 4.0

Page: 1/11 (30090856/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

ISO-BUTYRALDEHYDE

Recommended use of the chemical and restriction on use

Recommended use*: for industrial use only Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

<u>Company:</u> BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: aldehydes

2. Hazards Identification


According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	2	Flammable liquids
Eye Irrit.	2B	Eye irritation
Aquatic Acute	3	Hazardous to the aquatic environment - acute

Label elements

Revision date: 2024/07/24 Version: 4.0



Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

isobutyraldehyde CAS Number: 78-84-2 Content (W/W): > 99.5% Synonym: 2-Methylpropanal

Revision date: 2024/07/24 Version: 4.0

4. First-Aid Measures

Description of first aid measures

General advice:

Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). If not breathing, give artificial respiration. First aid personnel should pay attention to their own safety.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

If irritation develops, seek medical attention.

If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

If swallowed:

Rinse mouth and then drink 200-300 ml of water.

Do not induce vomiting. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, dyspnea, coughing Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: alcohol-resistant foam, carbon dioxide, dry powder

Unsuitable extinguishing media for safety reasons: water spray

Additional information: Water jet can rapidly spread fire.

Special hazards arising from the substance or mixture

Revision date: 2024/07/24 Version: 4.0

Hazards during fire-fighting:

Vapours may form explosive mixture with air. Cool endangered containers with water-spray. Risk of bursting. Burning produces harmful and toxic fumes.

Advice for fire-fighters

Protective equipment for fire-fighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Impact Sensitivity:

Remarks:

Based on the chemical structure there is no shock-sensitivity.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame. Keep people away and stay on the upwind side. Breathing protection required.

Environmental precautions

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Protect from air. Ensure thorough ventilation of stores and work areas.

Handle in accordance with good industrial hygiene and safety practice. Ground and/or bond all equipment to prevent electrostatic charges. Avoid all sources of ignition: heat, sparks, open flame.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

When containers are opened, flammable vapours may be released. Empty containers may contain flammable residue. Keep away from sources of ignition - No smoking.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), glass, Stainless steel 1.4301 (V2), Stainless steel 1.4401, High density polyethylene (HDPE)

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Protect from air.

Revision date: 2024/07/24 Version: 4.0

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour respirator.

Hand protection:

Chemical resistant protective gloves, Suitable materials, butyl rubber

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Avoid inhalation of vapour. Handle in accordance with good industrial hygiene and safety practice. Eye wash fountains and safety showers must be easily accessible.

9. Physical and Chemical Properties

Form: Odour: Odour threshold: Colour: pH value: Melting point:	liquid pungent odour No applicable information available. colourless to yellowish not applicable -65.9 °C	
Freezing point:	Literature data. No data available.	
Boiling point:	64 °C (1,013.25 hPa)	(measured)
Sublimation point:	No applicable information available.	
Flash point:	-24 °C	(DIN 51755, closed cup)
Flammability:	Highly flammable.	(derived from flash - and boiling point)
Lower explosion limit:	1.6 %(V)	
Upper explosion limit:	11.0 %(V)	
Autoignition:	180 °C	(ASTM E659)
Vapour pressure:	230.65 hPa (25 °C)	(measured)
Density:	Literature data. 0.78 g/cm3 (25.8 °C)	
Relative density:	0.78 (25.8 °C)	
Vapour density:	No applicable information available.	

Revision date: 2024/07/24 Version: 4.0 Page: 6/11 (30090856/SDS_GEN_US/EN)

Partitioning coefficient n- octanol/water (log Pow): Self-ignition temperature:	0.77 (25 °C) Based on its structural properties the product is not classified as self- igniting.	(OECD Guideline 107)
Thermal decomposition:	No decomposition if stored and handled a prescribed/indicated.	S
Viscosity, dynamic:	0.43 mPa.s (20 °C)	(DIN EN ISO 3219, Annex A)
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	60 g/l	
	(25 °C, 1,013.25 hPa)	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	72.11 g/mol	
Evaporation rate:	No applicable information available.	

10. Stability and Reactivity

Reactivity

No applicable information available.

Corrosion to metals: No corrosive effect on metal.

Oxidizing properties:Based on its structural properties the product is not classified as oxidizing.Formation ofRemarks:flammable gases:Forms no flammable gases in the

Chemical stability

No applicable information available.

Possibility of hazardous reactions

When finely distributed, self-ignition is possible.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

acids, bases, amines, oxidizing agents

Hazardous decomposition products

Decomposition products: Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Revision date: 2024/07/24 Version: 4.0

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

<u>Oral</u> Type of value: LD50 Species: rat Value: 3,730 mg/kg An aqueous solution was tested.

Inhalation Type of value: LC50 Species: rat (male) Value: > 23.9 mg/l (similar to OECD guideline 403) Exposure time: 4 h The vapour was tested.

Dermal Type of value: LD50 Species: rabbit Value: 5,583 mg/kg

<u>Assessment other acute effects</u> No applicable information available.

Irritation / corrosion Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation.

<u>Skin</u> Species: rabbit Result: non-irritant Method: OECD Guideline 404

<u>Eye</u> Species: rabbit Result: Irritant.

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Mouse ear swelling test (MEST) Species: mouse Result: Non-sensitizing.

Aspiration Hazard No aspiration hazard expected.

Revision date: 2024/07/24 Version: 4.0

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the upper respiratory tract after repeated inhalation, as shown in animal studies. Overexposure may cause blood abnormalities.

Genetic toxicity

Assessment of mutagenicity: In the majority of studies performed with microorganisms and in mammalian cell culture, a mutagenic effect was not found. A mutagenic effect was also not observed in in vivo tests. The substance was not mutagenic in bacteria. The substance induced chromosomal aberrations in a mammalian cell culture test. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity: Repeated inhalative uptake of the substance did not cause damage to the reproductive organs. The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Other Information development of pulmonary edema

12. Ecological Information

Toxicity

Aquatic toxicity Assessment of aquatic toxicity: Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish LC50 (96 h) 31.39 mg/l, Brachydanio rerio (OECD Guideline 203, semistatic)

<u>Aquatic invertebrates</u> EC50 (48 h) 277 mg/l, Daphnia magna (Directive 79/831/EEC, static) The details of the toxic effect relate to the nominal concentration.

Aquatic plants EC50 (72 h) 43.68 mg/l (growth rate), (OECD Guideline 201, static)

EC10 (72 h) 14.33 mg/l (growth rate), (OECD Guideline 201, static)

Chronic toxicity to fish

Revision date: 2024/07/24 Version: 4.0

No data available regarding toxicity to fish.

<u>Chronic toxicity to aquatic invertebrates</u> EC10 (21 d) 2.42 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

<u>Assessment of terrestrial toxicity</u> No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

<u>Toxicity to microorganisms</u> Oxygen consumption test aquatic activated sludge, domestic/No observed effect concentration (14 d): 100 mg/l

DIN 38412 Part 8 aquatic bacterium/EC50 (17 h): 468 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O) Readily biodegradable (according to OECD criteria).

Elimination information

80 - 90 % BOD of the ThOD (14 d) (OECD 301C; ISO 9408; 92/69/EWG, C.4-F) (aerobic, Inoculum conforming to MITI requirements (OECD 301C))

<u>Assessment of stability in water</u> According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis) No data available.

Bioaccumulative potential

<u>Assessment bioaccumulation potential</u> Significant accumulation in organisms is not to be expected.

Bioaccumulation potential No data available.

Mobility in soil

<u>Assessment transport between environmental compartments</u> The substance will slowly evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

Additional information

Sum parameter

Chemical oxygen demand (COD): 1,992 mg/g

Adsorbable organically-bound halogen(AOX): This product contains no organically-bound halogen. Revision date: 2024/07/24 Version: 4.0

13. Disposal considerations

Waste disposal of substance:

Dispose of in a RCRA-licensed facility. Do not discharge into waterways or sewer systems without proper authorization. Dispose of in accordance with national, state and local regulations.

Container disposal:

Empty containers with less than 1 inch of residue may be landfilled at a licensed facility. Dispose of container and any rinsate in an environmentally safe manner. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

RCRA: D001

14. Transport Information

Land transport USDOT Hazard class: Packing group: ID number: Hazard label: Proper shipping name:	3 II UN 2045 3 ISOBUTYL ALDEHYDE (ISOBUTYRALDEHYDE)
Sea transport IMDG Hazard class: Packing group: ID number: Hazard label: Marine pollutant: Proper shipping name:	3 II UN 2045 3 NO ISOBUTYL ALDEHYDE (ISOBUTYRALDEHYDE)
Air transport IATA/ICAO Hazard class: Packing group: ID number: Hazard label: Proper shipping name:	3 II UN 2045 3 ISOBUTYRALDEHYDE

15. Regulatory Information

Federal Regulations

Registration status:ChemicalTSCA, USreleased / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Revision date: 2024/07/24 Version: 4.0

Page: 11/11 (30090856/SDS GEN US/EN)

<u>CERCLA RQ</u> 100 LBS	<u>CAS Number</u> 78-84-2; 123-72-8	<u>Chemical name</u> isobutyraldehyde; butyraldehyde
<u>State regulations State RTK</u> PA NJ	ons <u>CAS Number</u> 78-84-2 78-84-2	<u>Chemical name</u> isobutyraldehyde isobutyraldehyde
NFPA Hazard Health: 2	codes: Fire: 3 Reactivity	/: 1 Special:
HMIS III rating Health: 2		nysical hazard: 1

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2024/07/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. OR THAT THE PRODUCTS. DESIGNS. DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET