

Safety data sheet

Page: 1/47

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022

Product: Sodium Nitrite FG 0,3% SiO2

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sodium Nitrite FG 0,3% SiO2

UFI: MVWU-U0H9-R00F-4DTA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: food additive(s)

Recommended use: Raw material, Intermediate, food additive(s), corrosion inhibitor, Surface

treatment agent

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Ox. Sol. 3 H272 May intensify fire; oxidizer.

Acute Tox. 3 (oral) H301 Toxic if swallowed.

Eye Dam./Irrit. 2 H319 Causes serious eye irritation. Aquatic Acute 1 H400 Very toxic to aquatic life.

M-factor acute: 1

According to BASF current knowledge and application of the criteria given in Annex I of Regulation (EC) No. 1272/2008, the following classification exceeding the classification given in Regulation (EC) No 1272/2008, Annex VI, Table 3.1 is required.

Ox. Sol. 2

Acute Tox. 3 (oral) Eye Dam./Irrit. 2 Aquatic Acute 1

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:







Signal Word:

Danger

Hazard Statement:

H319 Causes serious eye irritation.

H301 Toxic if swallowed.
H400 Very toxic to aquatic life.
H272 May intensify fire; oxidizer.

Precautionary Statements (Prevention):

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection or face protection.

P283 Wear fire resistant or flame retardant clothing.

P280 Wear eye and face protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P270 Do not eat, drink or smoke when using this product.
P264 Wash contaminated body parts thoroughly after handling.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

P221 Take any precaution to avoid mixing with combustibles ...
P220 Keep away from clothing and other combustible materials.

Precautionary Statements (Response):

P310 Immediately call a POISON CENTER or physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P301 IF SWALLOWED:
P330 Rinse mouth.
P391 Collect spillage.
P337 If eye irritation persists:

P311 Call a POISON CENTER or physician.

P370 + P378 In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):
P405 Store locked up.
P420 Store separately.
Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazard determining component(s) for labelling: sodium nitrite

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. No specific dangers known, if the regulations/notes for storage and handling are considered. The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

sodium nitriteNaNO2

to Regulation (EC) No 1907/2006.

Version: 1.2 Previous version: 1.1

Date / Revised: 24.11.2023
Date previous version: 31.03.2023
Date / First version: 16.12.2022
Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Contains:anticaking agent, free flowing agent

Regulatory relevant ingredients

sodium nitrite

Content (W/W): >= 75 % - <= 100 Ox. Sol. 3

% Acute Tox. 3 (oral)
CAS Number: 7632-00-0 Eye Dam./Irrit. 2
EC-Number: 231-555-9 Aquatic Acute 1

REACH registration number: 01- M-factor acute: 1 2119471836-27 H272, H319, H301, H400

<u>Differing classification according to current</u> knowledge and the criteria given in Annex I of

Regulation (EC) No. 1272/2008

Ox. Sol. 2

Acute Tox. 3 (oral) Eye Dam./Irrit. 2 Aquatic Acute 1

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2

Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: Risk of pulmonary edema. Symptoms can appear later. Danger of methaemoglobin formation after ingestion.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray

Unsuitable extinguishing media for safety reasons:

ABC powder, carbon dioxide

5.2. Special hazards arising from the substance or mixture

Endangering substances: nitrogen oxides

Advice: The substances/groups of substances mentioned can be released in case of fire. Has a fire-promoting effect due to release of oxygen.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Substance/product is an oxidizing agent and can supply oxygen to stimulate or accelerate the combustion of organic or other combustible substances/products.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use breathing apparatus if exposed to vapours/dust/aerosol. Avoid contact with eyes.

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

6.2. Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into waterways or sewer systems without proper authorization.

6.3. Methods and material for containment and cleaning up

For residues: Pick up with suitable appliance and dispose of.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Keep container tightly sealed. Breathing must be protected when large quantities are decanted without local exhaust ventilation. Processing machines must be fitted with local exhaust ventilation. Protect against moisture. Protect against heat. Do not mix with combustible substances. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

The substance/product is non-combustible. Has a fire-promoting effect due to release of oxygen. Where required Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from oxidizable substances. Segregate from acids. Segregate from ammonium salts.

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4541, Stainless steel 1.4571, High density polyethylene (HDPE), Low density polyethylene (LDPE), rubberized Further information on storage conditions: Keep container tightly closed and in a well-ventilated place. This product is classified as a dangerous substance for storage. The authority permits and storage regulations must be observed. Keep away from food, drink and animal feeding stuffs.

Storage class according to TRGS 510 (originally VCI, Germany): (5.1B) Oxidising substances

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

PNEC

freshwater: 0,0054 mg/l

marine water: 0,00616 mg/l

intermittent release: 0,0054 mg/l

sediment (freshwater): 0,0195 mg/kg

sediment (marine water): 0,0223 mg/kg

soil: 0,000733 mg/kg

STP: 21 mg/l

DNEL

worker:

Long- and short-term exposure - systemic effects, Inhalation: 2 mg/m3

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed. Particle filter with high efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P3 or FFP3).

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding > 480 minutes of permeation time according to EN ISO 374-1):

polyvinylchloride (PVC) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

chloroprene rubber (CR) - 0.5 mm coating thickness

butyl rubber (butyl) - 0.7 mm coating thickness

fluoroelastomer (FKM) - 0.7 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

to Regulation (EC) No 1907/2006.

Version: 1.2 Previous version: 1.1

Date / Revised: 24.11.2023
Date previous version: 31.03.2023
Date / First version: 16.12.2022
Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not breathe dust. Keep away from food, drink and animal feeding stuffs. No eating, drinking, smoking or tobacco use at the place of work. Take off immediately all contaminated clothing. Hands and/or face should be washed before breaks and at the end of the shift.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: solid Form: crystalline

Colour: white to slightly yellow

Odour: odourless

Odour threshold:

Not determined due to potential

health hazard by inhalation.

Melting point: 280 °C

Boiling point:

(1.013,25 hPa)

The substance / product decomposes therefore not

determined.

Flammability: not highly flammable (other)

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Flash point:

Study scientifically not justified.

Thermal decomposition: > 320 °C

Nitrogen monoxide, nitrogen dioxide, Disodium oxide

(other)

pH value: approx. 7 - 9

(100 g/l)

The product has not been tested.

The statement has been derived from substances/products of a similar

structure or composition.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Viscosity, kinematic:

not applicable, the product is a solid

Viscosity, dynamic:

Study scientifically not justified., not applicable, the product is a solid readily soluble. Formation of

Solubility in water: readily soluble, Formation of

sediments

Partitioning coefficient n-octanol/water (log Kow):

Study scientifically not justified.

Vapour pressure:

Study scientifically not justified.

Relative density: 2,17

(20 °C)

Literature data.

Density: 2,17 g/cm3 (ISO 2811-3)

(20 °C)

Information based on the main

component/s.

Relative vapour density (air):

The product is a non-volatile solid.

Particle characteristics

Particle size distribution: 200 - 400 µm (D50, measured)

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: Based on the chemical structure

there is no indication of explosive

properties.

Impact sensitivity: not shock-sensitive

Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Oxidizing., maximum burning rate (UN Test O.1 (oxidizing solids))

equal or higher than reference

mixture

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of

spontaneous heating.

Corrosion to metals

Corrosive effects to metal are not anticipated. - In the presence of

water or moisture metal corrosion cannot be excluded.

Other safety characteristics

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Radioactivity:

not radioactive for transport

purposes

Bulk density:

1.100 - 1.300 kg/m3

(other)

pKA:

Study scientifically not justified.

Hygroscopy:

hygroscopic

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

Evaporation rate:

The product is a non-volatile solid.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: Corrosive effects to metal are not anticipated. In the presence of water or

moisture metal corrosion cannot be excluded.

10.2. Chemical stability

The product is chemically stable.

10.3. Possibility of hazardous reactions

Hazardous reactions in presence of mentioned substances to avoid.

The product is stable if stored and handled as prescribed/indicated. Reacts with organic substances.

10.4. Conditions to avoid

See SDS section 7 - Handling and storage.

10.5. Incompatible materials

Substances to avoid:

reducing agents, oxidizable substances, ammonium salts, amines, amine compounds, acids

10.6. Hazardous decomposition products

Hazardous decomposition products:

Disodium oxide

nitrogen oxides

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of high toxicity after single ingestion. There is a risk of damage to the blood (methemoglobinemia) after a single uptake.

Experimental/calculated data:

LD50 rat (oral): 180 mg/kg

(by inhalation): Study scientifically not justified. (dermal): Study scientifically not justified.

Irritation

Assessment of irritating effects:

Not irritating to the skin. Eye contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation

rabbit: Irritant. (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

There is no evidence of a skin-sensitizing potential.

Experimental/calculated data:

Study scientifically not justified.

Germ cell mutagenicity

Assessment of mutagenicity:

The data available on mutagenic action are not consistent.

Carcinogenicity

Assessment of carcinogenicity:

In long-term studies in rats and mice in which the substance was given by drinking-water, a carcinogenic effect was not observed. Under certain conditions nitrites can enhance the formation of nitrosamines in vivo. Nitrosamines are carcinogenic in animal studies.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Developmental toxicity

Assessment of teratogenicity:

In animal studies the substance did not cause malformations. Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. After the uptake of small doses toxicity to development will not be expected in humans.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

There is a risk of damage to the blood (methemoglobinemia) after a single uptake.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

After repeated administration the prominent effect is damage of the blood (methemoglobin formation).

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

Very toxic (acute effect) to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 0,54 - 26,3 mg/l, Salmo gairdneri, syn. O. mykiss (other, Flow through.)

Aquatic invertebrates:

Date / Revised: 24.11.2023 Version: 1.2

Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

LC50 (96 h) 4,93 mg/l, aquatic crustacea (static) Literature data.

EC50 (48 h) 15,4 mg/l, Daphnia magna (OECD Guideline 202, part 1, static) The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants:

EC50 (72 h) > 100 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201, static) The statement of the toxic effect relates to the analytically determined concentration.

Microorganisms/Effect on activated sludge:

EC10 (3 h) 210 mg/l, activated sludge, domestic (OECD Guideline 209, static)

The details of the toxic effect relate to the nominal concentration.

EC50 (48 h) 421 mg/l, protozoa (other, static)

Chronic toxicity to fish:

No observed effect concentration (31 d) 6,16 mg/l, Ictalurus punctatus, syn: I. robustus (other, Flow through.)

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (80 d) 9,86 mg/l, aquatic crustacea (Daphnia test chronic, static)

Assessment of terrestrial toxicity:

No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

Not applicable for inorganic substances.

Elimination information:

not applicable

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis): not applicable

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Accumulation in organisms is not to be expected.

Bioaccumulation potential:

Date / Revised: 24.11.2023 Version: 1.2

Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.8. Additional information

Other ecotoxicological advice:

Do not allow to enter soil, waterways or waste water channels. Do not release untreated into natural waters. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Contact manufacturer regarding recycling. Check for possible recycling. Contact waste centre regarding recycling.

Contaminated packaging:

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Contaminated packaging should be emptied as far as possible and disposed of in accordance with official regulations after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1500

UN proper shipping name: SODIUM NITRITE

Transport hazard class(es): 5.1, 6.1, EHSM

Packing group: III Environmental hazards: yes

Special precautions for Tunnel code: E

user:

RID

UN number or ID number: UN1500

UN proper shipping name: SODIUM NITRITE

Transport hazard class(es): 5.1, 6.1, EHSM

Packing group: III Environmental hazards: yes

Special precautions for None known

user:

Inland waterway transport

ADN

UN number or ID number: UN1500

UN proper shipping name: SODIUM NITRITE

Transport hazard class(es): 5.1, 6.1, EHSM

Packing group: III Environmental hazards: yes

Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Sea transport

IMDG

UN number or ID number: UN 1500

UN proper shipping name: SODIUM NITRITE

Transport hazard class(es): 5.1, 6.1, EHSM

Packing group: III Environmental hazards: yes

Marine pollutant: YES

Special precautions for EmS: F-A; S-Q

user:

Air transport

IATA/ICAO

UN number or ID number: UN 1500

UN proper shipping name: SODIUM NITRITE

Transport hazard class(es): 5.1, 6.1 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

to Regulation (EC) No 1907/2006. Date / Revised: 24.11.2023

Date previous version: 31.03.2023

Version: 1.2 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Chemical Prohibition Ordinance (DE): Annex 2 Restriction Type: Restricted substance

Hazardous Incident Ordinance (Germany):

List entry in regulation: 1.1.2 List entry in regulation: 1.2.8 List entry in regulation: 1.3.1

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: E1 List entry in regulation: H2 List entry in regulation: P8

Classification according to 'TA-Luft' (Germany):

5.2.1: total dust, including fine dust

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (3) Strongly water polluting.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Ox. Sol. 2 Acute Tox. 3 (oral)

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Eye Dam./Irrit. 2A Aquatic Acute 1

M-factor acute: 1

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Ox. Sol. Oxidising solids Acute Tox. Acute toxicity

Eye Dam./Irrit. Serious eye damage/eye irritation

Aquatic Acute Hazardous to the aquatic environment - acute

H319 Causes serious eye irritation.

H301 Toxic if swallowed.
H400 Very toxic to aquatic life.
H272 May intensify fire; oxidizer.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Annex: Exposure Scenarios

Index

- **1.** Formulation & (re)packing of substances and mixtures, (handling as solid), Industrial applications IS; IS, SU9; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC19, PROC26, PROC15
- 2. Formulation & (re)packing of substances and mixtures, (handling as solid in solution), (handling as melted mass), Industrial applications

IS; IS, SU10; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC15, PROC19, PROC26

- **3.** Formulation & (re)packing of substances and mixtures, (handling as solid), Professional applications PW; IS, SU10; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC15, PROC19, PROC26
- **4.** Formulation & (re)packing of substances and mixtures, (handling as solid in solution), (handling as melted mass), Professional applications

PW; IS, SU8, SU9; ERC2; PROC3, PROC4, PROC8b, PROC9, PROC5, PROC15, PROC19, PROC26

- **5.** Use as an intermediate, Use in chemical synthesis, Industrial applications IS; IS, SU8, SU9; ERC6a; PROC3, PROC4, PROC8b, PROC15, PROC26
- **6.** Use in Metallurgy, Use for Heat storage, Industrial applications IS; SU15; ERC7; PROC3, PROC4, PROC9, PROC25
- **7.** Use as Corrosion inhibitor, (use in professional settings) PW; SU2b, IS, SU17, PW; ERC7; PROC5, PROC17, PROC20
- **8.** Use in Metal surface treatment, (use in industrial settings), (handling as solid)
- IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
- **9.** Use in Metal surface treatment, (handling as solid in solution), (handling as melted mass), (use in industrial settings)
- IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

* * * * * * * * * * * * * * * *

1. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (handling as solid), Industrial applications IS; IS, SU9; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC19, PROC26, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises PROC5: Mixing or blending in batch processes PROC15: Use a laboratory reagent. Use domain: industrial

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to	o its source	
PROC4, PROC5		
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,5 mg/m³	
Risk Characterization Ratio (RCR)	0,25	
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.	
PROC9, PROC15	term raide maniphed by a factor of 21	
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,05	
`	The short-term exposure value corresponds to the long-	
	term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	g/tra	

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m ³
Risk Characterization Ratio (RCR)	0,25
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	'tra

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into sma containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		
Exposure estimate and reference to	o its source	
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,05	
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	g/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

	Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to	its source	
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,5 mg/m ³	
Risk Characterization Ratio (RCR)	0,25	
	The short-term exposure value corresponds to the long-	
	term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	tra	

Contributing exposure scenario		
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Worker - contact with eyes	
Additional good practice advice	
In case of possible exposure towards degradation products use a suitable respiratory protection	
Avoid release of degradation products	

Contributing exposure scenario		
Use descriptors covered	ERC2: Formulation into mi	xture
Operational conditions		
Annual amount per site	700.000 kg	
Minimum emission days per year Continuous	300	
Emission factor air	0 %	
Emission factor water	2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Treat wastewater (prior to discharge to STP) to provide the required removal efficiency of (%)		99 %
Wastewater treatment measures consider	dered suitable are, e.g.	Oxidation
Type of STP		Municipal STP
Estimated subst. removal from wastewater via sewage treatm. (%)		87,3 %
Total effic. of removal from wastewater after RMMs and STP(%)		87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to	its source	
Assessment method	EUSES v2.1	
Maximum amount of safe use	4.257 kg/d	
Risk from environmental exposure is dr	iven by freshwater.	

* * * * * * * * * * * * * * * *

2. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (handling as solid in solution), (handling as melted mass), Industrial applications

IS; IS, SU10; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC15, PROC19, PROC26

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk characterisation.		
Exposure estimate and reference to its source		

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Assessment method	Qualitative assessment
	Worker - contact with eyes
Additional good practice advice	
In case of possible exposure towards degradation products use a suitable respiratory protection	
Avoid release of degradation products	

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15: Use a laboratory reagent. Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
	sodium nitrite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid in solution, Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	
generated.	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contribution and a superior		
Contributing exposure scenario		
	PROC19: Manual activities involving hand contact	
	Use domain: industrial Solid in solution. For non-spraying	
Use descriptors covered	processes (no aerosol generation), an inhalative exposure	
	is considered to be not relevant.	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
	65/16/18/19 76 X 166 76	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable chemically resistant		
gloves.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario		
Use descriptors covered	ERC2: Formulation into mi	xture
Operational conditions	l	
Annual amount per site	700.000 kg	
Minimum emission days per year Continuous	300	
Emission factor air	0 %	
Emission factor water	2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Treat wastewater (prior to discharge to STP) to provide the required removal efficiency of (%)		99 %
Wastewater treatment measures consid	lered suitable are, e.g.	Oxidation
Type of STP		Municipal STP
Estimated subst. removal from wastewater via sewage treatm. (%)		87,3 %
Total effic. of removal from wastewater after RMMs and STP(%)		87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EUSES v2.1	
Maximum amount of safe use	4.257 kg/d	

Page: 28/47

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Baseletian (EQ) No. 1007/2006

to Regulation (EC) No 1907/2006.

Version: 1.2 Previous version: 1.1

Date / Revised: 24.11.2023 Date previous version: 31.03.2023 Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Risk from environmental exposure is driven by freshwater.	

* * * * * * * * * * * * * * * *

3. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (handling as solid), Professional applications PW; IS, SU10; ERC2; PROC4, PROC5, PROC8b, PROC9, PROC15, PROC19, PROC26

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 90 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	Application duration: 480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
PROC4, PROC5	
Assessment method	ECETOC TRA v2.0 Worker; modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,9 mg/m³
Risk Characterization Ratio (RCR)	0,45
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.
Assessment method	Qualitative assessment
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra
Please note that a modified version ha	as been used (see exposure estimates)

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

	discharging) at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC15: Use a laboratory reagent. PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
	sodium nitrite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	Application duration: 480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	•
Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	o its source
PROC8b, PROC9, PROC19	
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,25
	The short-term exposure value corresponds to the
	ECETOC TRA initial exposure value multiplied by a factor
	of 2.
PROC15	
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,05
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: professional covered by PROC8b covered by PROC9 covered by PROC5

Contributing exposure scenario

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Use descriptors covered	ERC2: Formulation into mi	xture
Operational conditions		
Annual amount per site	700.000 kg	
Minimum emission days per year Continuous	300	
Emission factor air	0 %	
Emission factor water	2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Treat wastewater (prior to discharge to STP) to provide the required removal efficiency of (%)		99 %
Wastewater treatment measures consi	dered suitable are, e.g.	Oxidation
Type of STP		Municipal STP
Estimated subst. removal from wastew		87,3 %
Total effic. of removal from wastewater	\ /	87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EUSES v2.1	
Maximum amount of safe use	4.257 kg/d	
Risk from environmental exposure is driven by freshwater.		

* * * * * * * * * * * * * * * *

4. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (handling as solid in solution), (handling as melted mass), Professional applications

PW; IS, SU8, SU9; ERC2; PROC3, PROC4, PROC8b, PROC9, PROC5, PROC15, PROC19, PROC26

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for
	exposure arises PROC5: Mixing or blending in batch

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

	processes PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC15: Use a laboratory reagent. PROC19: Manual activities involving hand contact PROC26: Handling of solid inorganic substances at ambient temperature Use domain: professional Solid in solution. For nonspraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures	,	
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture
Operational conditions	
Annual amount per site	700.000 kg
Minimum emission days per year Continuous	300
Emission factor air	0 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10

to Regulation (EC) No 1907/2006.

Version: 1.2 Previous version: 1.1

Date / Revised: 24.11.2023 Date previous version: 31.03.2023 Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Treat wastewater (prior to discharge to STP) to provide the required removal efficiency of (%)		99 %
Wastewater treatment measures consid	lered suitable are, e.g.	Oxidation
Type of STP		Municipal STP
Estimated subst. removal from wastewater via sewage treatm. (%)		87,3 %
Total effic. of removal from wastewater after RMMs and STP(%)		87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EUSES v2.1	
	4.257	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by freshwater.		

* * * * * * * * * * * * * * * *

5. Short title of exposure scenario

Use as an intermediate, Use in chemical synthesis, Industrial applications IS; IS, SU8, SU9; ERC6a; PROC3, PROC4, PROC8b, PROC15, PROC26

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Exposure estimate and reference to its source	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Additional good practice advice	
In case of possible exposure towards degradation products use a suitable respiratory protection	
Avoid release of degradation products	

Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures	,	
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15: Use a laboratory reagent. Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %
Physical state	Solid in solution, Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	

Version: 1.2

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023

Date previous version: 31.03.2023 Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Previous version: 1.1

generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
	sodium nitrite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid in solution, Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	
generated.	
Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
Assessment method	Qualitative assessment
	Worker - contact with eyes
Additional good practice advice	
In case of possible exposure towards d	egradation products use a suitable respiratory protection
Avoid release of degradation products	

Contributing exposure scenario		
Use descriptors covered	ERC6a: Use of intermediate	
Operational conditions	•	
Annual amount per site	8.000.000 kg	
Minimum emission days per year Continuous	300	
Emission factor air	0 %	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Emission factor water	0,05 %			
Emission factor soil	0 %			
Receive Surf. Water (Flow Rate).	400.000 m3/d			
Dilution factor river	40			
Dilution factor coast	400			
Other Factors: Environment	Indoor and outdoor use.			
Risk Management Measures	Risk Management Measures			
Type of STP		Municipal STP		
Assumed sewage treatment plant flow	sewage treatment plant flow (m3/d)			
Exposure estimate and reference to	Exposure estimate and reference to its source			
Assessment method	EUSES v2.1			
Risk Characterization Ratio (RCR)	0,803			
	Risk from environmental exposure is driven by freshwater.			
	26.692			
Maximum amount of safe use	kg/d			
Risk from environmental exposure is driven by freshwater.				

* * * * * * * * * * * * * * *

6. Short title of exposure scenario

Use in Metallurgy, Use for Heat storage, Industrial applications IS; SU15; ERC7; PROC3, PROC4, PROC9, PROC25

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %
Physical state	Solid in solution, Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %
	25
Physical state	Solid in solution, Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	
generated.	
Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
Assessment method	Qualitative assessment
	Worker - contact with eyes
Additional good practice advice	
In case of possible exposure towards d	egradation products use a suitable respiratory protection
Avoid release of degradation products	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to	its source	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
·	PROC25: Other hot work operations with metals
Use descriptors covered	Exposure is considered negligible.
Operational conditions	I
	sodium nitrite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Melted mass
Risk Management Measures	
Ensure that no inhalable aerosols are	
generated.	
Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
Assessment method	Qualitative assessment
	Worker - contact with eyes
	Exposure is considered negligible.
Additional good practice advice	· · ·
• •	egradation products use a suitable respiratory protection

Contributing exposure scenario		
Use descriptors covered	ERC7: Use of functional fluid at industrial site	
Operational conditions		
Annual amount per site	1.500.000 kg	
Minimum emission days per year Continuous	0	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Emission factor air	0,00 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Other Factors: Environment	Indoor and outdoor use.		
Risk Management Measures			
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EUSES v2.1		

* * * * * * * * * * * * * * * *

7. Short title of exposure scenario

Use as Corrosion inhibitor, (use in professional settings) PW; SU2b, IS, SU17, PW; ERC7; PROC5, PROC17, PROC20

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes PROC17: Lubrication at high energy conditions in metal working operations PROC20: Use of functional fluids in small devices Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 10 %	
Physical state	Solid in solution	
Risk Management Measures		
Ensure segregation of worker from the source		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Additional good practice advice

In case of possible exposure towards degradation products use a suitable respiratory protection Avoid release of degradation products

Contributing exposure scenario		
	ERC7: Use of functional fluid at industrial site	
Use descriptors covered	The environmental release is considered negligible.	
Operational conditions		
Annual amount per site	1.500.000 kg	
Minimum emission days per year Continuous	0	
Emission factor air	0,00 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EUSES v2.1	

* * * * * * * * * * * * * * *

8. Short title of exposure scenario

Use in Metal surface treatment, (use in industrial settings), (handling as solid) IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Operational conditions	
	sodium nitrite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	Application duration: 480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable eye protection.	
Risk Management Measures are	
based on qualitative risk	
characterisation.	
Exposure estimate and reference to	its source
PROC1	
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,005
· ·	The short-term exposure value corresponds to the long-
	term value multiplied by a factor of 2.
PROC8a	· ·
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m ³
Risk Characterization Ratio (RCR)	0,25
,	The short-term exposure value corresponds to the long-
	term value multiplied by a factor of 2.
PROC3	
Assessment method	ECETOC TRA v2.0 Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,05
, ,	The short-term exposure value corresponds to the long-
	term value multiplied by a factor of 2.
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	•
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises PROC5: Mixing or blending in batch processes PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium nitrite

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

	Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
PROC4, PROC5		
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,5 mg/m³	
Risk Characterization Ratio (RCR)	0,25	
	The short-term exposure value corresponds to the long-	
	term value multiplied by a factor of 2.	
PROC9, PROC15		
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,05	
	The short-term exposure value corresponds to the long-	
	term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	′tra	

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

characterisation.		
Exposure estimate and reference to its source		
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,5 mg/m ³	
Risk Characterization Ratio (RCR)	0,25	
	The short-term exposure value corresponds to the long-term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid – low dustiness	
Duration and Frequency of activity	Application duration: 480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	ECETOC TRA v2.0 Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,05	
	The short-term exposure value corresponds to the long- term value multiplied by a factor of 2.	
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
Operational conditions	

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

	OECD ESD No.12 used, as tonnage.	ssessment independent from
	100	
Minimum emission days per year Continuous		
Release to waste water from process	0,528 kg/d	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Type of STP		Municipal STP
Estimated subst. removal from wastewater via sewage treatm. (%)		87,3 %
Total effic. of removal from wastewater after RMMs and STP(%)		87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EUSES v2.1	·
Risk Characterization Ratio (RCR)	0,794	
	Risk from environmental ex	xposure is driven by freshwater.

* * * * * * * * * * * * * * * *

9. Short title of exposure scenario

Use in Metal surface treatment, (handling as solid in solution), (handling as melted mass), (use in industrial settings)

IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.
Operational conditions	
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %
Physical state	Solid in solution

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

0 (-1) (1		
Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario	
	PROC4: Chemical production where opportunity for
	exposure arises
Use descriptors covered	Use domain: industrial Solid in solution. For non-spraying
	processes (no aerosol generation), an inhalative exposure
	is considered to be not relevant.

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Operational conditions		
	sodium nitrite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		
Avoid release of degradation products		

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection Avoid release of degradation products		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15: Use a

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

	laboratory reagent. Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposure is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are		
generated.		
Use suitable eye protection.		
Risk Management Measures are		
based on qualitative risk		
characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection Avoid release of degradation products		

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial Solid in solution. For non-spraying processes (no aerosol generation), an inhalative exposur is considered to be not relevant.	
Operational conditions		
Concentration of the substance	sodium nitrite Content: >= 0 % - <= 100 %	
Physical state	Solid in solution, Melted mass	
Risk Management Measures		
Ensure that no inhalable aerosols are generated.		
Use suitable eye protection.		
Risk Management Measures are based on qualitative risk characterisation.		
Exposure estimate and reference to its source		
Assessment method	Qualitative assessment	
	Worker - contact with eyes	
Additional good practice advice		
In case of possible exposure towards degradation products use a suitable respiratory protection		

to Regulation (EC) No 1907/2006.

Date / Revised: 24.11.2023 Version: 1.2
Date previous version: 31.03.2023 Previous version: 1.1

Date / First version: 16.12.2022 Product: **Sodium Nitrite FG 0,3% SiO2**

(ID no. 30262349/SDS_GEN_DE/EN)

Date of print 06.03.2024

Avoid release of degradation products

Contributing exposure scenario		
•	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)	
Use descriptors covered		
Operational conditions		
	OECD ESD No.12 used, assessment independent from tonnage.	
Minimum emission days per year Continuous		
Release to waste water from process	0,528 kg/d	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Other Factors: Environment	Indoor and outdoor use.	
Risk Management Measures		
Type of STP		Municipal STP
Estimated subst. removal from wastewater via sewage treatm. (%)		87,3 %
Total effic. of removal from wastewater after RMMs and STP(%)		87,3 %
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to		
Assessment method	EUSES v2.1	
Risk Characterization Ratio (RCR)	0,794	
	Risk from environmental exposure is driven by freshwater.	

* * * * * * * * * * * * * * * *