

Safety data sheet

Page: 1/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Stearyl Methacrylate 1618 F (SMA 1618 F)

Chemical name: Reaction mass of hexadecyl methacrylate and octadecyl methacrylate

REACH registration number: 01-2119489777-13-0004, 01-2119489777-13-0002, 01-2119489776-15-0004, 01-2119489776-15-0002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monomer for manufacturing of polymers

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

<u>Company:</u> BASF SE 67056 Ludwigshafen GERMANY <u>Contact address:</u> BASF plc 4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG UNITED KINGDOM

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 2/34

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H335 May cause respiratory irritation.

Specific Concentration Limits According to Regulation (EC) No 1272/2008 [CLP]

STOT SE 3, irr. to respiratory syst.: >= 10 %

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word: Warning

Hazard Statement:	
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
Precautionary Statemer	nts (Prevention):
P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
Precautionary Statemer	nts (Response):
P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary Statemer	nts (Storage):
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
Precautionary Statemer	nts (Disposal):
P501	Dispose of contents and container to hazardous or special waste collection point.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 3/34

Hazard determining component(s) for labelling: Octadecyl methacrylate, Hexadecyl methacrylate

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

Reaction mass of hexadecyl methacrylate and octadecyl methacrylate

Hazardous ingredients (GHS)

Octadecyl methacrylate Content (W/W): >= 65 % - <= 70 % Skin Corr./Irrit. 2 CAS Number: 32360-05-7 Eye Dam./Irrit. 2 EC-Number: 251-013-5 STOT SE 3 (irr. t INDEX-Number: 607-134-00-4 H319, H315, H33

Skin Corr./Irrit. 2 Eye Dam./Irrit. 2 STOT SE 3 (irr. to respiratory syst.) H319, H315, H335

Specific concentration limit: STOT SE 3, irr. to respiratory syst.: >= 10 %

Hexadecyl methacrylate

	Page: 4/34
BASF Safety data sheet according to Regulation UP time to time.	K SI 2019/758 and UK SI 2020/1577 as amended from
Date / Revised: 28.08.2023	Version: 5.0
Date previous version: 20.10.2022	Previous version: 4.0
Date / First version: 16.04.2012	
Product: Stearyl Methacrylate 1618 F (SMA 1618	
	(ID no. 30530/37/SDS_GEN_GB/EN)
	Date of print 06.07.2025
Content (W/W): >= 25 % - <= 30 %	Skin Corr./Irrit. 2
CAS Number: 2495-27-4	Eye Dam./Irrit. 2
EC-Number: 219-672-3	STOT SE 3 (irr. to respiratory syst.)
INDEX-Number: 607-134-00-4	H319, H315, H335
	Specific concentration limit
	STOT SE 3, irr. to respiratory syst.: >= 10 %
Takes dated an other and take	
retradecyl methacrylate Content (W/W): >= 0.1 % - <= 5 %	Skin Corr /Irrit 2
CAS Number: 2549-53-3	Eve Dam /Irrit 2
EC-Number: 219-835-9	STOT SE 3 (irr. to respiratory syst.)
INDEX-Number: 607-134-00-4	H319, H315, H335
	O 1 1 1 1 1 1
	Specific concentration limit:
	STOT SE 3, III: to respiratory syst $\geq 10 \%$
Icosyl methacrylate	
Content (W/W): $>= 0 \% - <= 3 \%$	Skin Corr./Irrit. 2
EC Number: 256 220 4	Eye Dam./Imit. 2 STOT SE 2 (irr. to respiratory syst.)
INDEX-Number: 607-134-00-4	H319 H315 H335
	Specific concentration limit:
	STOT SE 3, irr. to respiratory syst.: >= 10 %

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact: Wash thoroughly with soap and water

Page: 5/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: **Stearyl Methacrylate 1618 F (SMA 1618 F)**

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons: water jet

Additional information: Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: Self-polymerization if overheated in a container. Cool endangered containers with waterspray.

Advice: The product is combustible. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 6/34

Forms slippery surfaces with water. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 7/34

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability: Storage temperature: 19 - 35 °C Storage duration: 12 Months The stated storage temperature should be noted. Avoid prolonged storage. This product should be processed as soon as possible. Ensure adequate inhibitor and dissolved oxygen level. Do not store with less than 10 % headspace above liquid. Storage stability is based upon ambient temperatures and conditions described. It is recommended to keep a safe distance of +2 degrees above the crystallization range. The product is stabilized, the shelf life should be noted.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 8/34

No substance specific occupational exposure limits known.

<u>PNEC</u>

A PNEC could not be derived as the substance showed no toxic effects in studies performed in the range of its solubility. At the present state of knowledge, no negative ecological effects are expected.

DNEL worker: Long-term exposure- systemic effects, dermal: 41.66 mg/kg

consumer: Long-term exposure- systemic effects, dermal: 25 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection: Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	white to slightly yellow	
Odour:	of fatty acid	
Odour threshold:	,	
	not determined	
pH value:		
P	of very low solubility not applicable	
Melting point:	16 °C	(Directive 92/69/EEC A 1)
Moning point.	(1.013 hPa)	
	The product has not been tested	
	The product has not been tested.	
	aubstances/products of a similar	
	substances/products of a similar	
de composition point.		
decomposition point:	$> 250^{-1}$	(Directive 92/69/EEC, A.2)
	(1,018 nPa)	
	The product has not been tested.	
	I ne statement has been derived from	
	substances/products of a similar	
	structure or composition.	
Flash point:	117 °C	(Directive 92/69/EEC, A.9,
	The product has not been tested.	closed cup)
	The statement has been derived from	
	substances/products of a similar	
	structure or composition.	
Evaporation rate:		
	Value can be approximated from	
	Henry's Law Constant or vapor	
	pressure.	
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:		
	For liquids not relevant for	
	classification and labelling., The	
	lower explosion point may be 5 - 15	
	°C below the flash point.	
Upper explosion limit:	•	
	For liquids not relevant for	
	classification and labelling.	

Page: 9/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F) (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025 260 °C Ignition temperature: (Directive 92/69/EEC, A.15) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. approx. 0.0006 hPa Vapour pressure: (20 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition., Literature data. Density: 0.869 g/cm3 (OECD Guideline 109) (20 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Relative density: 0.869 (OECD Guideline 109) (20 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Relative vapour density (air):> 1 (estimated) (20 °C) Heavier than air. Solubility in water: The product has not been tested. (other) The statement has been derived from substances/products of a similar structure or composition. < 1 µg/l (25 °C) Partitioning coefficient n-octanol/water (log Kow): 9.62 (calculated) (25 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Self ignition: Based on its structural properties the Test type: Spontaneous selfproduct is not classified as selfignition at room-temperature. igniting. Thermal decomposition: No decomposition if stored and handled as prescribed/indicated. Viscosity, kinematic: 11.7 mm2/s (OECD 114) (20 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Page: 10/34

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Explosion hazard:	Based on the chemical structure there is no indication of explosive properties	
Fire promoting properties	Based on its structural properties	(other)
r no promoting proportion	the product is not classified as	(00101)
	oxidizing.	

9.2. Other information

Self heating ability:	not applicable, the product is a liquid
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.
pKA:	
	The substance does not dissociate.
Hygroscopy:	Non-hygroscopic
:	
	No data available.
Surface tension:	
	Based on chemical structure, surface
	activity is not to be expected.
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.
Molar mass:	338.57 g/mol

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: Corrosive effects to metal are not anticipated.

Formation of	Remarks:	Forms no flammable gases in the
flammable gases:		presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Peroxides: 0 % The product does not contain peroxides.

10.3. Possibility of hazardous reactions

Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized.

Polymerization coupled with heat formation.

Page: 11/34

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 12/34

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat.

Reacts with nitric acid. Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated. 10.4. Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures.

10.5. Incompatible materials

Substances to avoid:

radical formers, free radical initiators, peroxides, oxidizing agents, reducing agents, strong bases, strong acids

Inert gas

10.6. Hazardous decomposition products

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Of low toxicity after short-term skin contact. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data: LD50 rat (oral): > 5,000 mg/kg (OECD Guideline 401) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

(by inhalation): Study not necessary due to exposure considerations.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 13/34

LD50 rabbit (dermal): > 3,000 mg/kg (other) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation

Assessment of irritating effects: The European Union (EU) has classified the substance as "irritating to skin and eyes".

Experimental/calculated data: Skin corrosion/irritation rabbit: non-irritant (other) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Serious eye damage/irritation rabbit: non-irritant (OECD Guideline 405) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: Non-sensitizing. (OECD Guideline 429) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects. The chemical structure does not suggest a specific alert for such an effect.

Reproductive toxicity

Assessment of reproduction toxicity:

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 14/34

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Assessment of STOT single: The European Union (EU) has classified the substance as "causing irritation of the respiratory tract"

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

The information available on the product provides no indication of toxicity on target organs after repeated exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Toxicity to fish:

LC0 (96 h) > 10,000 mg/l, Brachydanio rerio (OECD Guideline 203, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LC0 (96 h) > 10,000 mg/l, Brachydanio rerio (OECD Guideline 203, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Aquatic invertebrates: No data available.

Aquatic plants:

EC50 (72 h) > 10 μ g/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Microorganisms/Effect on activated sludge:

EC50 (180 min) > 10,000 mg/l, activated sludge, domestic (OECD Guideline 209, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to fish: No data available.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) >= $5.73 \mu g/l$, Daphnia magna (OECD Guideline 211, semistatic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of terrestrial toxicity: No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): Readily biodegradable (according to OECD criteria). The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Elimination information:

79 % CO2 formation relative to the theoretical value (28 d) (OECD 301C; ISO 9408; 92/69/EEC, C.4-F) (activated sludge)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of stability in water: No data available. Study scientifically not justified. Information on Stability in Water (Hydrolysis): No data available.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential: Does not accumulate in organisms.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 16/34

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Bioaccumulation potential:

Bioconcentration factor (BCF): 37 (56 h), Brachydanio rerio (OECD Guideline 305 E) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12.4. Mobility in soil

Assessment transport between environmental compartments: Volatility: No data available. Adsorption in soil: No data available. Study scientifically not justified.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria.

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Not fulfilling vPvB (very persistent/very bioaccummulative) criteria.

12.6. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

Other ecotoxicological advice: Do not discharge product into the environment without control.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging: Disposal must be made according to official regulations.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for	None known
user	

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for	None known
user	

Inland waterway transport ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for	None known
user:	

Transport in inland waterway vessel Not evaluated

Sea transport

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

IMDG

user

Not classified as a dangerous good under transport regulations UN number or ID number: Not applicable Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Special precautions for None known

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations UN number or ID number: Not applicable UN proper shipping name: Not applicable Not applicable Transport hazard class(es): Packing group: Not applicable Environmental hazards: Not applicable Special precautions for None known user

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

Page: 18/34

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

15.2. Chemical Safety Assessment

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 5 (dermal)

 Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

 Skin Corr./Irrit.
 Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation	
STOT SE Specific target organ toxicity — single	exposure
H319 Causes serious eye irritation.	-
H315 Causes skin irritation.	
H335 May cause respiratory irritation.	

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population.

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 20/34

TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Page: 21/34

Annex: Exposure Scenarios

Index

1. Polymer production, Formulation, (use in industrial settings) SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9

2. Use as laboratory reagent/agent, (use in industrial settings) SU24, SU8, SU9; ERC1; PROC15

3. Use in/as Formulation, Use as Monomer, (use in industrial settings) SU10, SU12; ERC6c; PROC5, PROC7, PROC9, PROC19

4. Use in/as Formulation, Use as Monomer, (use in professional settings) SU10, SU12, SU19; ERC8c, ERC8f; PROC5, PROC9, PROC10, PROC11, PROC19

* * * * * * * * * * * * * * * *

1. Short title of exposure scenario

Polymer production, Formulation, (use in industrial settings) SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

Operational conditions

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.06 Pa
Process temperature	20 °C

Page: 22/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: **Stearyl Methacrylate 1618 F (SMA 1618 F)**

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

480 min 5 days per week Duration and Frequency of activity Indoor/Outdoor Indoor Risk Management Measures Use suitable chemically resistant Effectiveness: 80 % gloves. Avoid skin contact. Exposure estimate and reference to its source Assessment method EASY TRA v4.1, ECETOC TRA v3.0, Worker Worker - dermal, long-term - systemic Exposure estimate 0.0069 mg/kg bw/day Risk Characterization Ratio (RCR) 0.000165 Qualitative assessment Assessment method Worker - inhalation Guidance to Downstream Users

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0.2743 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.006584	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Page: 23/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0.1371 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.003292	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0.06 Pa
during use	
Process temperature	20 °C

Page: 24/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Previous version: 4.0 Date previous version: 20.10.2022 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1.3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.03292	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to	ts source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	2.7429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.065839	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Page: 25/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	2.7429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.065839	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	

Page: 26/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN)

Date of print 06.07.2025

Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	2.7429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.065839	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions	·	
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1.3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.03292	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

2. Short title of exposure scenario

Use as laboratory reagent/agent, (use in industrial settings) SU24, SU8, SU9; ERC1; PROC15

Control of exposure and risk management measures

Contributing exposure scenario ERC1: Manufacture of the substance		
ERC1: Manufacture of the substance	Contributing exposure scenario	
Use descriptors coveredAs no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.	Use descriptors covered	ERC1: Manufacture of the substance As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

Operational conditions

Contributing exposure scenario		
	PROC15: Use a laboratory reagent.	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	Reaction mass of hexadecyl methacrylate and octadecyl	
Concentration of the substance	methacrylate	
	Content: >= 0 % - <= 100 %	
Physical state	liquid	
during use	0.06 Pa	
	20 °C	
Process temperature		
	480 min 5 days per week	
Duration and Frequency of activity		
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant	Effectiveness: 80 %	
gloves.		
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0.0686 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.001646	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

* * * * * * * * * * * * * * * *

3. Short title of exposure scenario

Page: 27/34

> (ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Use in/as Formulation, Use as Monomer, (use in industrial settings) SU10, SU12; ERC6c; PROC5, PROC7, PROC9, PROC19

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

Operational conditions

Contributing exposure scenario		
	PROC5: Mixing or blending in batch processes	
Use descriptors covered	Use domain: industrial	
Oneretional conditions		
Operational conditions		
	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	2.7429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.065839	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	

Page: 29/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	8.5714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.205747	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
Vapour pressure of the substance during use Process temperature Duration and Frequency of activity Indoor/Outdoor Risk Management Measures Use suitable chemically resistant gloves. Avoid skin contact. Exposure estimate and reference to in Assessment method Exposure estimate Risk Characterization Ratio (RCR) Assessment method	0.06 Pa 20 °C 480 min 5 days per week Indoor Effectiveness: 80 % <i>ts source</i> EASY TRA v4.1, ECETOC TRA v3.0, Worker Worker - dermal, long-term - systemic 8.5714 mg/kg bw/day 0.205747 Qualitative assessment Worker - inhalation	

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		

Page: 30/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.03292
Assessment method	Qualitative assessment
	Worker - inhalation
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario		
	PROC19: Manual activities involving hand contact	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	Reaction mass of bevadecyl methacrylate and octadecyl	
	methacrulate	
Concentration of the substance	Content: $> -0\% - < -100\%$	
Physical state	liquid	
Vapour pressure of the substance	0.06 Pa	
during use		
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant	Effectiveness: 80 %	
gloves.		
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	28.2857 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.678966	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

* * * * * * * * * * * * * * * *

4. Short title of exposure scenario

Use in/as Formulation, Use as Monomer, (use in professional settings) SU10, SU12, SU19; ERC8c, ERC8f; PROC5, PROC9, PROC10, PROC11, PROC19

Control of exposure and risk management measures

Contributing exposure scenario

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Use descriptors covered As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.	Use descriptors covered	ERC8c: Widespread use leading to inclusion into/onto article (indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
---	-------------------------	---

Operational conditions

Contributing exposure scenario	
Use descriptors covered	ERC8f: Widespread use leading to inclusion into/onto article (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

Operational conditions

Contributing exposure scenario		
	PROC5: Mixing or blending in batch processes	
Use descriptors covered	Use domain: professional	
Operational conditions		
	Reaction mass of hexadecyl methacrylate and octadecyl	
Or a contraction of the contractor	methacrylate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vanour pressure of the substance	0.06 Pa	
during use	0.00 F a	
Process temporature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant	Effectiveness: 80 %	
gloves.	Effectiveness. 80 78	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	2.7429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.065839	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario

Page: 32/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN)

Date of print 06.07.2025

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1.3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.03292	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario		
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional	
Operational conditions		
Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		

Page: 33/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: **Stearyl Methacrylate 1618 F (SMA 1618 F)**

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Use suitable chemically resistant gloves.	Effectiveness: 80 %	
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	5.4857 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.131678	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario PROC11: Non industrial spraying Use descriptors covered Use domain: professional **Operational conditions** Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Concentration of the substance Content: >= 0 % - <= 100 % Physical state liquid Vapour pressure of the substance 0.06 Pa during use 20 °C Process temperature 480 min 5 days per week Duration and Frequency of activity Indoor/Outdoor Indoor **Risk Management Measures** Use suitable chemically resistant Effectiveness: 80 % gloves. Avoid skin contact. Exposure estimate and reference to its source EASY TRA v4.1, ECETOC TRA v3.0, Worker Assessment method Worker - dermal, long-term - systemic 21.4286 mg/kg bw/day Exposure estimate Risk Characterization Ratio (RCR) 0.514368 Assessment method Qualitative assessment Worker - inhalation

Guidance to Downstream Users For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	

Page: 34/34

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.08.2023 Version: 5.0 Date previous version: 20.10.2022 Previous version: 4.0 Date / First version: 16.04.2012 Product: Stearyl Methacrylate 1618 F (SMA 1618 F)

(ID no. 30530737/SDS_GEN_GB/EN) Date of print 06.07.2025

Concentration of the substance	Reaction mass of hexadecyl methacrylate and octadecyl methacrylate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0.06 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Use suitable chemically resistant	Effectiveness: 80 %	
gloves.		
Avoid skin contact.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	28.2857 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0.678966	
Assessment method	Qualitative assessment	
	Worker - inhalation	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

* * * * * * * * * * * * * * * *