

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 1/11

(30801703/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## Isobutyl Acrylate Wide Spec

#### Recommended use of the chemical and restriction on use

Recommended use\*: Chemical used in synthesis and/or formulation of industrial products

Recommended use\*: industrial chemicals

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: acrylates

### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

Flam. Liq.	3	Flammable liquids
Acute Tox.	4 (Inhalation - vapour)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1B	Skin sensitization

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 2/11

(30801703/SDS\_GEN\_US/EN)

STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear eye protection.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use extinguishing powder, foam or CO2 for extinction.

Precautionary Statements (Storage):

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 3/11

(30801703/SDS\_GEN\_US/EN)

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

### Hazards not otherwise classified

Labeling of special preparations (GHS):

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %

Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration).

## 3. Composition / Information on Ingredients

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

isobutylacrylate

CAS Number: 106-63-8

Content (W/W):  $\geq 75.0$  -  $\leq 100.0\%$

Synonym: 2-Propenoic acid 2-methylpropyl ester; Isobutyl acrylate

n-butyl acrylate

CAS Number: 141-32-2

Content (W/W):  $\geq 0.3$  -  $< 25.0\%$

Synonym: 2-Propenoic acid butyl ester; Butyl acrylate

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

#### If on skin:

Wash thoroughly with soap and water

#### If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. Seek medical attention.

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 4/11  
(30801703/SDS\_GEN\_US/EN)

*Information on: isobutylacrylate*

*Symptoms: Overexposure may cause:, CNS stimulation, respiratory disorders, collapse, salivation*

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, dry powder, foam

Unsuitable extinguishing media for safety reasons:  
water

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Risk of violent self-polymerization if overheated in a container.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Fight fire from maximum distance. If exposed to fire, keep containers cool by spraying with water.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Take appropriate protective measures.

Ensure adequate ventilation. Use personal protective clothing. Breathing protection required.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Substance/product is RCRA hazardous due to its properties.

### Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

For large amounts: Pump off product.

Dispose of in accordance with national, state and local regulations.

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 5/11  
(30801703/SDS\_GEN\_US/EN)

### 7. Handling and Storage

#### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Protection against fire and explosion:

Sealed containers should be protected against heat as this results in pressure build-up. Heated containers should be cooled to prevent polymerization.

#### Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Keep container tightly closed. Keep locked-up and out of reach of children.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Avoid UV-light and other radiation with high energy. Protect against contamination. In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 35 °C

Storage duration: 12 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

The product is stabilized, the shelf life should be noted.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

n-butyl acrylate                      ACGIH, US:    TWA value 2 ppm ;

#### Personal protective equipment

##### Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

##### Hand protection:

Wear chemical resistant protective gloves.

##### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 6/11  
(30801703/SDS\_GEN\_US/EN)

### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

### General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	ester-like	
Colour:	almost colourless	
pH value:	of low solubility	
Freezing point:	No data available.	
Melting point:	No data available.	
Boiling range:	137.8 - 147 °C ( 1.013 hPa)	
Boiling point:	No data available.	
Flash point:	36 °C	(open cup)
Flammability:	Flammable.	
Autoignition:	275 °C	
Vapour pressure:	9.6 hPa ( 25 °C)	
Density:	0.8896 - 0.8915 g/cm <sup>3</sup> ( 25 °C)	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	0.82 - 0.88 mPa.s ( 21 °C)	
Solubility in water:	1.7 - 1.8 g/l ( 25 °C)	
Miscibility with water:	of low solubility	

## 10. Stability and Reactivity

### Reactivity

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Risk of spontaneous polymerization when heated or in the presence of UV radiation. With unstabilised product, spontaneous polymerisation may occur e.g. through ambient heat.

Polymerization coupled with heat formation. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase.

Radical formation can cause exothermic polymerization. Reacts with peroxides and other radical components. Risk of spontaneous polymerization in the presence of starters for radical chain

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 7/11

(30801703/SDS\_GEN\_US/EN)

reactions (e.g. peroxides). Reacts with nitric acid. Polymerizes explosively in contact with strong oxidizing agents. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Do not blanket with nitrogen.

Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage.

Avoid inhibitor loss. Avoid excessive temperatures.

### Incompatible materials

polyvinylchloride, radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, acid anhydrides, acid chlorides, concentrated mineral acids

Inert gas

### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation.

*Information on: isobutylacrylate*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Of moderate toxicity after short-term inhalation. Of low toxicity after short-term skin contact.*

*Information on: n-butyl acrylate*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of low toxicity after single ingestion. Of low toxicity after short-term skin contact.*

#### Oral

Type of value: ATE

Value: > 5,000 mg/kg

#### Inhalation

Type of value: ATE

Value: 10.6 mg/l

Determined for vapor

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 8/11  
(30801703/SDS\_GEN\_US/EN)

Type of value: ATE  
Value: 1.51 mg/l  
Determined for mist

### Dermal

Type of value: ATE  
Value: > 5,000 mg/kg

### Assessment other acute effects

Assessment of STOT single:  
Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

*Information on: isobutylacrylate*

*Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes.*

*Information on: n-butyl acrylate*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

-----

### Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

*Information on: isobutylacrylate*

*Assessment of sensitization:*

*Sensitization after skin contact possible. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: n-butyl acrylate*

*Assessment of sensitization:*

*Sensitization after skin contact possible.*

-----

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

*Information on: isobutylacrylate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the olfactory epithelium after repeated inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: n-butyl acrylate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the olfactory epithelium after repeated inhalation.*

-----

### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.



# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 9/11

(30801703/SDS\_GEN\_US/EN)

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity

*Information on: isobutylacrylate*

*Assessment of aquatic toxicity:*

*Acutely toxic for aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.*

*The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.*

*Information on: n-butyl acrylate*

*Assessment of aquatic toxicity:*

*Acutely toxic for aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.*

### Additional information

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

## 13. Disposal considerations

### Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations.

### Container disposal:

Dispose of in accordance with national, state and local regulations.

## 14. Transport Information

### Land transport

USDOT

Hazard class: 3

Packing group: III

ID number: UN 2527

Hazard label: 3

Proper shipping name: ISOBUTYL ACRYLATE, STABILIZED MIXTURE

### Sea transport

IMDG

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 10/11

(30801703/SDS\_GEN\_US/EN)

Hazard class: 3  
Packing group: III  
ID number: UN 2527  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: ISOBUTYL ACRYLATE, STABILIZED MIXTURE

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 2527  
Hazard label: 3  
Proper shipping name: ISOBUTYL ACRYLATE, STABILIZED MIXTURE

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

#### EPCRA 313:

##### CAS Number

141-32-2

##### Chemical name

n-butyl acrylate

##### CERCLA RQ

5000 LBS

##### CAS Number

71-36-3; 78-83-1;  
123-86-4; 110-19-  
0

##### Chemical name

n-butanol; Isobutanol; n-Butyl acetate; isobutyl acetate

100 LBS

106-63-8

isobutylacrylate

### State regulations

##### State RTK

NJ

##### CAS Number

106-63-8

##### Chemical name

isobutylacrylate

141-32-2

n-butyl acrylate

PA

106-63-8

isobutylacrylate

141-32-2

n-butyl acrylate

#### NFPA Hazard codes:

Health: 2

Fire: 3

Reactivity: 2

Special:

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2022/06/10

# Safety Data Sheet

## Isobutyl Acrylate Wide Spec

Revision date : 2022/06/10

Version: 1.0

Page: 11/11

(30801703/SDS\_GEN\_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET