

Foamaster[®] NO 2335

general

defoamer based on renewable raw materials

- excellent defoamer for mat to satin-finished aqueous coatings
- environmentally sound alternative to defoamers based on mineral oil
- retains antifoaming properties even after prolonged storage of the finished paint
- exceptional product stability
- quick foam suppression when used in latex production

chemical nature

blend of hydrophobic components and natural oils

Properties

physical form

yellowish hazy liquid

storage

Foamaster[®] NO 2335 should be stored in a cool dry place.

During storage of Foamaster[®] NO 2335 a slight sedimentation or phase separation might occur.

The defoaming properties of Foamaster[®] NO 2335 are not affected, if the product is mixed thoroughly prior to use.

typical properties (no supply specification)

density at 20 °C (68 °F)	~ 0.9 g/cm ³
Brookfield viscosity at 23 °C (73 °F)	~ 875 mPa·s
solubility in water	insoluble

Application

Foamaster[®] NO 2335 is a defoamer based on renewable raw materials. It is an excellent defoamer for mat to satin-finished aqueous coatings based on synthetic latex, plasters based on organo silicates, and aqueous adhesives.

recommended concentrations

0.1 – 0.4% on total formulation

When manufacturing paints, Foamaster[®] NO 2335 is best added during grinding in order to achieve perfect incorporation of the defoamer into the system. In emulsion polymerization, add defoamer directly on the foam.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America

BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Foamaster® NO 2335.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives