

Basoflux[®] PI 3120

Paraffin inhibitor for crude oil

July 2021 | Data Sheet | First Edition

TI-EVG 0333e / Page 1 of 4

® = registered trademark of BASF SE

Description

Basoflux[®] PI 3120 is a polyacrylate that is modified with Behenyl carbon chains and dissolved in an aliphatic mineral spirit.

Principal Uses

Basoflux[®] PI 3120 is primarily used as a paraffin inhibitor or rheology improver in the crude oil production segment, and aims to reduce the crude oil pour point, inhibit paraffin deposition, and/or lower the yield stress of the crude oil.

While conducting pour point testing, it is highly recommended to dose the paraffin inhibitor into the crude oil sample above the wax appearance temperature (WAT).

The paraffin inhibitor treat rate is crude oil dependent, typically ranging from several hundred ppm to greater than 2000 ppm for more challenging and highly paraffinic crude oils.

When melted, Basoflux[®] PI 3120 is a low viscosity product. In addition, the product has a higher flash point than Toluene and Xylene, resulting in less hazardous handling.


Typical properties

Appearance at 23°C:	Amber solid
Relative molecular weight	High
Relative chain length	C ₂₂₊
Active concentration (%)	50%
Density (g/cm ³)	Approx. 0.9
Viscosity (mPa.s @ 40°C)	240
Melting point (°C)	~37°C
Pour point (°C)	~32°C
Flash point (°C):	> 61°C
Organic solvent	Shellsol D70

Application

Basoflux® PI 3120 can be applied in the field by dilution with typical solvents such as naphtha based aromatic solvents, Xylene or Toluene, but also aliphatic mineral spirits.

The viscosities using Xylene are displayed in the graph below.



Solubility & Stability

Solubility behaviour of the Basoflux® PI 3120 after 28 days is displayed below with respect to time, temperature, and dilution factor.


Legend: S: solid, L: liquid,

Product	Solvent	Xylene			Solvesso 150 ND		
		4°C	25°C	40°C	4°C	25°C	40°C
100	0	S	S	L	S	S	L
80	20	S	S	L	S	S	L
70	30	S	S	L	S	S	L
60	40	S	L	L	S	S	L
50	50	S	L	L	S	S	L
40	60	S	L	L	S	L	L
30	70	S	L	L	S	L	L
20	80	S	L	L	S	L	L
10	90	S	L	L	S	L	L

Performance

Basoflux® PI 3120 performance has been extensively tested in the laboratory and has been selected for various applications, mostly in combination with other Basoflux® paraffin inhibitors to benefit from the synergistic effects.

Performance as flow improver



Basoflux® PI 3120 paraffin inhibitor performance on a difficult to treat crude oil sample provided by a service company. The customer challenged BASF to develop a better performing flow improver than the incumbent.

Performance as PPD in crude oil

Sample	Dosage, Product [ppm]	NFP Ø [°C]	Δ NFP [°C]	PP [°C]
Blank	0	24,1		27
Basoflux PI 3120	1000	15,5	8,6	18

Basoflux PI 3120 reduced the pour point from 27°C to 18°C in the crude oil.

Storage	Store in unopened original containers in a well-ventilated place. Keep container dry.
Shelf life	Basoflux® PI 3120 is stable for approx 36 months in its original sealed packaging
Shipping	Basoflux® PI 3120 is available in 200-liter steel drums or in 20-tons bulk ISO containers. Other packaging can be considered subject to discussion. When shipped in ISO containers these should be equipped with heating possibilities.
Handling	Basoflux® PI 3120, when at low ambient temperature and in solid state, can be melted by heating the product. Heating can be carried out either (1) in a water bath at ~70 °C, (2) in a heated room (40 to 50 °C) or (3) with a heating jacket. Exposure of Basoflux® PI 3120 to prolonged and excessive heat may cause product deterioration.
Health & Safety	Please refer to the Safety Data Sheet (SDS) for detailed information concerning product's hazards and appropriate protective measures in the workplace
Technical service	Advice and assistance in the application and performance of Basoflux® PI 3120 is available from BASF experienced in oilfield representatives.
Note	The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

July 2021

oilfieldchemicals@basf.com
www.oilfield-chemicals.basf.com

Europe BASF SE Global Oilfield Chemicals Carl-Bosch-Str. 38 67056 Ludwigshafen Germany Phone: +49 621 60-0	North America BASF Corporation Global Oilfield Chemicals 3120 Hayes Road Suite 200 Houston, TX 77082 USA Phone: +1 800 7941019	South America Oilfield Chemicals BASF S.A. Avenida das Nações Unidas 14.171 Morumbi 04794-000 São Paulo Brazil Phone: +55 11 2039-2583	Asia Pacific Oilfield Chemicals BASF South East Asia Pte. Ltd 33 Tuas Avenue 11 Singapore 639090 Phone: +65 6860 7052	China Oilfield Chemicals BASF (China) Co. Ltd 333 Jiangxinsha Road Pudong Shanghai 200137 China Phone: +86 755 2681 8972	Middle East BASF FZE P.O. Box 61309 Jebel Ali Free Zone Dubai United Arab Emirates Phone: +971 4 807 2154
--	---	--	---	---	---