

Prosorb N

Sulfur Guard Bed Adsorbent

BASF Prosorb N, used as sulfur guard beds for naphtha reformers and isomerization units, is a next generation Nickel based adsorbent which provides significant performance improvement for removal of trace levels of various sulfur species

BASF Prosorb N is produced as special high surface area tri-lobed extrudates with a nominal diameter of 1/16" (1.6 mm). It is delivered pre-reduced and passivated.

Prosorb N boasts higher sulfur capacity including up to 50% higher removal for thiols and up to 100% higher removal efficiencies for thiophene as compared to competitive Ni based guard beds. Typical operating temperatures range from 140-170°C.

Value drivers

1. Protects downstream equipment and maximizes mileage as well as yield of downstream catalysts
2. Non-selective removal of sulfurs with very high capacity
3. Longer bed life compared to competitive materials, requiring fewer costly changeouts which require downtime
4. Higher capacity and better performance compared to Cu based adsorbent, without running the risk of Cu leaching

Product Applications

1. Removal of various broad range of sulfur species (H₂S, COS, mercaptans, sulfides, disulfides and thiophenes) from feed streams typically used in naphtha reformers and isomerization units.
2. Sacrificial sulfur adsorbent for streams containing difficult to remove / broadest range of organosulfurs

Typical Properties

Ni, wt %	~ 59%
Surface Area, m ² /g	~ 185
Packed Average Bulk Density, kg/m ³ (lbs/ft ³)	~ 800 (~ 50)
Bulk Crush Strength	~ 0.9 MPa (~131 psi)

Pre-Treatment


Prior to start-up, the bed must be activated by removing the passivation. This can be performed via hydrogen activation, nitrogen activation, or by using the feed to be treated (hot oil activation). Maximum performance is achieved via hydrogen activation at temperatures of 150 – 180°C.

Packaging

- Steel drum, 125 kg (275 lbs) net

Shipping Point

- De Meern, The Netherlands



Relative Capacity of Prosorb N vs Competition

About Us

BASF's Catalysts division is the world's leading supplier of environmental and process catalysts. The group offers exceptional expertise in the development of technologies that protect the air we breathe, produce the fuels that power our world and ensure efficient production of a wide variety of chemicals, plastics and other products, including advanced battery materials. By leveraging our industry-leading R&D platforms, passion for innovation and deep knowledge of precious and base metals, BASF's Catalysts division develops unique, proprietary solutions that drive customer success.

BASF - We create chemistry

Americas

BASF Corporation
25 Middlesex/Essex Turnpike
Iselin, New Jersey, 08830, USA
Tel : +1-732-205-5000
Fax: +1-732-205-7725
Email: catalysts-america@basf.com

Asia Pacific

BASF (China) Company Limited
300 Jiang Xin Sha Road,
Pudong, Shanghai 200137
P.R. China
Tel: +86-21-2039 2549
Fax: +86-21-2039 4800-2549
Email: catalysts-asia@basf.com

Europe, Middle East, Africa

BASF De Meern BV Catalysts
The Netherlands
Tel: +31-30-666 9437
Email: catalysts-europe@basf.com

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2015 BASF