

Acronal[®] A 200

Polymer Dispersions for Construction

Chemical nature Pure acrylate dispersion, manufactured without the addition of APEO

Properties

Physical form liquid

Technical data

(not supply specification)

Solids content	DIN EN ISO 3251	67 – 71%
pH value	DIN ISO 976	6.5 – 8.0
Viscosity	DIN EN ISO 3219 (100 1/s, 23 °C)	150 – 500 mPa s
Glas temperature		~ -43 °C

Application

Areas of application

Due to its high tack Acronal® A 200 is very suitable for flooring fixations.

Additionally, we recommend Acronal® A 200 for the manufacture of resin-free adhesives for flexible floorings.

Due to its low inherent smell and also due to the applicability in resin-free formulations, Acronal® A 200 is especially recommended for low-odor adhesives.

Acronal® A 200 is suitable for low VOC emission formulations (Emicode® EC1 or even EC1PLUS). Furthermore, it can be used in products with the Blue Angel (DE-UZ-113).

Processing

In the manufacture of flooring adhesives based on Acronal® A 200 the dispersion is put into a mixer and then dispersant (e. g. Dispex® AA 4135), antifoam (e. g. FoamStar® SI 2210) and thickening agent (e.g. Rheovis® AS 1125) are added; finally, the fillers are stirred in. If a strong alkaline solution or ammonia is added, the viscosity rises considerably. We recommend adding preservatives to adhesives that contain Acronal® A 200 to protect them from microbial attack.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

BASF SE

Dispersions & Resins Europe
67056 Ludwigshafen, Germany
www.basf.com/dispersions