

## Tough Plastics for Dunnage

When shipping your valuable, precision parts, BASF has the solutions you need to protect them. Elastocast® elastomers, Elastofoam® i-skins, Elastollan® TPU and Elastocoat® elastomeric spray systems provide rugged, durable high strength protection for every possible configuration.

### Benefits

- High chemical and moisture resistance
- Superior tear and abrasion resistance
- The most durable solution available
- Compatible with high and low pressure dispensing equipment
- Robust processing properties
- One ISO for solid and i-skin formulations

### Typical Applications

- Reusable racks and containers
- Returnable packaging

### ISO's for Both Technologies:

- Elastofoam® 3120T
- Elastoflex® 3092T

### Why is BASF the First Choice in Returnable Dunnage?



#### Breadth of Portfolio

All the solutions you need – PU Elastomers, TPU, Foam, Elastomeric coatings & Engineering Plastics



#### Multiple Isocyanate Solutions

Isocyanates to fit your performance requirements and equipment or one isocyanate for foam and elastomer



#### Processing & Equipment Knowledge

More than a material provider – in-house prototyping, start-up assistance



#### Partnership – Start to Finish

Experience formulators and tech service invested in you



#### Low Environmental Impact Systems

All foam systems utilize near zero GWP blowing agents

	Hardness (Shore A)	Foam Density (PCF)	Die C Tear (PLI)	Split Tear (PLI)	Tensile Strength (PSI)	Ultimate Elongation (%)	Notes
--	--------------------	--------------------	------------------	------------------	------------------------	-------------------------	-------

### Standard Integral Skin Solutions

Elastofoam® 38751R/3120T	35-65	15-25	28-48	10-18	200-400	180-200	<ul style="list-style-type: none"> <li>All standard systems utilize HFO blowing agents.</li> <li>Other systems can be supplied without blowing agents</li> <li>Customized formulations available to target specific properties</li> <li>Prototype parts can be made using BASF's Hennecke dispensing machine</li> </ul>
Elastofoam® 38850R/3120T	65	27	64	26	495	230	
Elastofoam® 38650R/3120T	75	27	68	35	550	90	
Elastofoam® 38660R/3120T	90	27	120	53	890	80	

### Standard Polyurethane Elastomer Solutions

#### Standard Performance Grades

Elastocast® 72470R/3092T	70A	–	210	–	2500	350	<ul style="list-style-type: none"> <li>Customization available to meet specific customer requirements</li> <li>Resin and ISO options to dial in required performance for low- and high-pressure machines</li> <li>Superior load bearing and damping properties</li> </ul>
Elastofoam® 37310R/3120T	90A	–	300	–	2100	450	
Elastocast® 72740R/3092T	90A	–	340	–	2500	500	
Elastocast® R4A972/3092T	97A	–	550	–	2700	200	
Elastocast® R4D65/3092T	65D	–	500	–	3500	110	

#### High Performance Grades

Elastocast® R4A90E/3092T	90	–	450	–	4960	400
Elastocast® R4A95E/3092T	95	–	589	–	5500	396

	Hardness	Tensile Strength (PSI)	Die C Tear (PLI)	Ultimate Elongation (%)	Taber Abrasion (mg loss)	Din Abrasion (mm <sup>3</sup> loss)	Notes
--	----------	------------------------	------------------	-------------------------	--------------------------	-------------------------------------	-------

### Standard TPU Solutions

Elastollan® S90AN	90A	6200	830	540	25	30	<ul style="list-style-type: none"> <li>Many other grades in ester and ether backbone resins are available for custom applications</li> <li>Superior cut, tear and abrasion resistance properties</li> <li>Excellent damping properties and high resiliency</li> </ul>
Elastollan® S95AN	93A	6600	950	500	30	30	
Elastollan® S60DN	60D	7300	1300	400	50	25	

## Notes

Please contact our technical service department for more help on formulating with products from the Elastofoam®, Elastocast® and Elastollan® product line.

BASF Corporation, Wyandotte, MI

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. When handling these products, advice and information given in the safety data sheet must be complied with. Further, protective and workplace hygiene measures adequate for handling chemicals must be observed. (01/2018)

® = Registered trademark of the BASF Group