

Dispex Ultra[®] FA 4430

general • nonionic surfactant used to improve the storage stability of emulsion paints and their compatibility with cement and lime.

chemical nature ethoxylate of a fatty alcohol in water

Properties

physical form liquid

storage a cloudiness or precipitation can appear during storage at temperatures lower than 20°C. This effect is reversible at temperatures higher than 25°C.

typical properties (no supply specification)	pH value	~ 6.5
	color (Hazen)	~ 100
	water	~ 70%

Application

Dispex Ultra[®] FA 4430 is a nonionic surfactant used to improve the storage stability of emulsion paints and their compatibility with cement and lime. It can be used in interior paints, exterior paints and textured finishes. Dispex Ultra[®] FA 4430 offers performance highlights such as:

- excellent improvement of compatibility with cement and lime
- improvement of storage stability
- easier cleaning of equipment

recommended concentrations An addition level of about 0.3% - 1.0% in relation to the final formulation is recommended.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

South America

BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Dispex Ultra FA 4430.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives