

Efka[®] SL 3210



general

slip and leveling agent

- very effective additive to increase substrate wetting, slip, surface smoothness and gloss.
- good compatibility with a broad range of printing ink systems
- relatively insensitive to pin-holing – even at high dosage

chemical nature

organically modified polysiloxane

Properties

physical form

clear colorless liquid

storage

Efka[®] SL 3210 should be stored in a cool dry place.

**typical properties
(no supply specification)**

active ingredients > 95 %

Application

Efka[®] SL 3210 is compatible with a broad range of formulation polarities. It may be used in water-based, solvent-based and UV-curable printing inks and overprint varnishes.

Efka[®] SL 3210 is effective in nitrocellulose-based systems for flexographic and gravure printing as well as in UV-curable applications ranging from flexographic printing inks to clear overprint varnishes.

recommended concentrations

0.1–0.3 % on total formulation

In some cases dosages above 0.3 % can be used. Appropriate levels should always be determined based on the end use of the ink or varnish. Levels are dependent on required effects but also depend on whether an ink has to be overprinted.

Efka[®] SL 3210 can be added at any stage during the production process. When added during dispersion, it speeds up pigment wetting.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

South America

BASF S.A
Rochavérá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Efka® SL 3210.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives