

Rheovis[®] PU 1216

Product description Rheology modifier

- Key benefits**
- Non-ionic medium pseudoplastic rheology modifier for water-based coatings
 - Improved flow and gloss
 - Increase in hiding power
 - Wash and scrub resistance
 - Outstanding spatter resistance during roller application

Chemical nature Polyurethane polymer in water/ 1,2-propylene glycol

Properties

Physical form Whitish, viscous liquid

Technical data (not supply specification)	Solid content	DIN ISO 1625 (105 °C, 2h)	~ 43 %
	Viscosity	ISO 2555, Brookfield, 25 °C	~ 20 Pa.s
	Density	at 20 °C	~ 1.08 g/cm ³

Application

Rheovis® PU 1216 is suitable for the thickening and modification of the flow properties of water-based polymers (e.g. acrylic copolymers, vinyl acetate homopolymers, acrylic polymers, PVAc/VAE copolymers, polyurethanes, amine-neutralized and emulsified systems) as well as for products based on polymeric binders such as emulsion paints, texture finishes, high-gloss emulsions paints, water-based putties, adhesives and corrosion primers.

Formulation guideline 0.2 – 2.0 % on total formulation

Undiluted Rheovis® PU 1216 can be incorporated into the system while stirring. Cuts in butyl glycol or 1,2-propylene glycol are possible as well. It can be combined with other kinds of thickeners such as acrylics or cellulosic

Storage

Keep container tightly closed and store in a cool, dry place.
Protect from temperatures below 0 °C and above 40 °C

If stored at low temperatures freezing of the product is possible. This process is reversible. Please heat product to room temperature and stir well before use.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Rheovis® PU 1216.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives