

Selexsorb® CDi

Improved Alumina based adsorbent for the removal of polar compounds

BASF Selexsorb® CDi is custom formulated to provide optimum adsorption of polar compounds from reactive olefinic streams.

BASF Selexsorb® CDi is available as spheres with nominal sizes of 7x14 Tyler mesh (approx. 1.6 mm) and 1/8" (approx. 3.2 mm).

Selexsorb® CDi provides the benefits of enhanced capacity for impurities with reduced surface activity and lower bulk density. Together they provide for longer life and overall higher capacity even towards end of life while reducing the amount of adsorbent needed. All parameters together will lead to a reduction of regeneration gas and energy needed increasing the sustainability of this product.

CDi is the new preferred Selexsorb® material for removing polar contaminants from reactive process streams, especially ethylene, propylene and butenes. Typical contaminants to be removed with Selexsorb® CDi include water, oxygenates (alcohols, aldehydes, ketones, ethers, peroxides), mercaptans, sulfides and nitrogen-based molecules (ammonia, amines, nitriles).

Product Applications

1. BASF Selexsorb® CDi is custom formulated to remove trace contaminants from feed monomer (ethylene, propylene), feed comonomer (α -olefins) and recycle solvent streams in polymer production processes including polyethylene and polypropylene. Polymerization catalyst deactivation is minimized through the removal of these contaminants with BASF's selective Adsorbents.

2. Removal of oxygenates from C4 raffinate stream used in metathesis processes is another important

application of this adsorbent. The removal of the oxygenates ensures optimal catalyst activity and life. Examples of such oxygenates are methanol, dimethyl ether, tertiary butyl alcohol, acetaldehyde and ketones. In the presence of reactive olefinic species Selexsorb® CDi offers better capacity and performance than Selexsorb® CD or CDL and thus is the preferred solution for these applications.

3. Hydrocarbon feed streams used in petrochemical or refining catalytic processes frequently contain trace contaminants that can adversely affect the performance of downstream catalysts. BASF Selexsorb® CDi is an excellent adsorbent for removing trace oxygenates, sulfides and mercaptans and other such species from feed streams to isomerization and alkylation processes.

Selexsorb® CDi can also be used in combination with Selexsorb® COS or Selexsorb® COSi. For further information, please contact BASF.

Chemical Composition

Al ₂ O ₃ plus proprietary modified	95.5
LoI (250 – 1 100°C)	4.0

Typical Physical Properties

Surface Area, m ² /g	440
Crush Strength, kg (lbs)	1,4 – 3,2 (3 – 7)
Bulk Density kg/m ³ (lbs/ft ³)	590 (37)

* These indicative properties do not represent process capabilities nor specifications.



We create chemistry

Product Data Sheet

For proper handling of the material, especially when bringing the adsorbent in contact with olefins, please contact BASF for further details.

Packaging

- FIBC (flexible intermediate bulk container), 680 kg / 1 500 lbs net
- Steel drum 125 kg / 276 lbs net

Shipping Point

- Vidalia, LA, USA, or
- Natchez, MS, USA (BASF warehouse)

About Us

BASF is a leading global manufacturer of catalysts for the chemical industry, with solutions across the chemical value chain. The business comprises chemical catalysts, adsorbents and custom catalysts. Priority is given to developing new and improved products that enable the chemical industry transformation to net-zero emissions.

BASF's chemical catalysts and adsorbents business is part of the company's Performance Chemicals division. The division's portfolio also includes refinery catalysts, fuel and lubricant solutions, as well as oilfield chemicals and mining solutions. Customers from a variety of industries including Chemicals, Plastics, Consumer Goods, Energy & Resources and Automotive & Transportation benefit from our innovative solutions.

BASF - We create chemistry



www.chemical-catalysts-and-adsorbents.basf.com/adsorbents

Americas

BASF Corporation
Phone: +1-732-205-5000
Email: catalysts-america@basf.com

Asia Pacific

BASF (China) Company Limited
Phone: +86-21-2039 2549
Email: catalysts-asia@basf.com

Europe, Middle East, Africa

BASF Services Europe GmbH
Phone: +49-30-2005 5000
Email: catalysts-europe@basf.com

Selexsorb is a registered trademark of BASF

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2015 BASF

BASF- 10766 - 11/2025