

# Formulation Additives

## Technical Data Sheet

# Foamaster<sup>®</sup> MO 2175 (old: Foamaster<sup>®</sup> 75)



**Product Description** Foamaster<sup>®</sup> MO 2175 is a new non-separating defoamer for flat to semi-gloss coatings that offers good persistency and knock down. It is a cost-effective alternative to silica-based defoamer.

**Chemical Composition** Defoamer

---

### Properties

<b>Typical Properties</b>	Moisture (N-171)	0.5 %
	Dispersibility (10% in water)	Non-Dispersible
	Density (T-013)	~ 7.2 lb/gal
	IR Identity (T-001)	Equal to Standard

**Typical Characteristics** Appearance Opaque off-white liquid

These typical values should not be interpreted as specifications.

---

### Applications

Foamaster<sup>®</sup> MO 2175 offers the following advantages:

- Non-separating and non-settling defoamer
- Cost-effective
- Good knock down of manufacturing foam
- Good long term persistency
- Minimal impact on coating surface properties

General purpose defoamer for flat to semi-gloss architectural coating.

---

### Safety

**General** The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

**Material Safety Data Sheet** All safety information is provided in the Material Safety Data Sheet for Foamaster<sup>®</sup> MO 2175.

---

## Storage

Foamaster® MO 2175 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. Foamaster® MO 2175 is shipped in 55 gallon (200 liter) open head steel drums. If subjected to below freezing temperatures, allow to warm to room temperature and mix well before using. Additional handling information is contained in a material safety data sheet which is available on request.

---

## Important

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the reader make tests to determine the suitability of a product for a particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.** In no case shall the descriptions, information, data or designs provided be considered a part of BASF's terms and conditions of sale. Further, the descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained all such being given and accepted at the reader's risk.

*Foamaster is a registered trademark of BASF Group.*

© BASF Corporation, 2015



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: [www.basf.us/responsiblecare\\_usa](http://www.basf.us/responsiblecare_usa)

Canada: [www.basf.us/responsiblecare\\_canada](http://www.basf.us/responsiblecare_canada)

México: [www.basf.us/responsiblecare\\_mexico](http://www.basf.us/responsiblecare_mexico)

BASF Corporation  
Dispersions and Pigments  
11501 Steele Creek Road  
Charlotte, North Carolina 28273  
Phone: (800) 251 – 0612  
Email: [edtech\\_info@basf.com](mailto:edtech_info@basf.com)  
[www.basf.us/dpsolutions](http://www.basf.us/dpsolutions)