

FoamStar[®] ST 2410

Product description FoamStar ST 2410 represents a novel series of defoamers based on new defoamer chemistry. It is the first new defoamer chemistry in over 30 years.

FoamStar is a defoaming molecule that defoams by a different mechanism. Unlike conventional defoamers (mineral oil or silicone), FoamStar defoams on a molecular level. It also has wetting properties not found in other conventional defoamers.

- Key benefits**
- Defoams at the molecular level
 - Has wetting properties not found in other conventional defoamers

Chemical nature Molecule compounded in an enhanced mineral-oil system

Properties

Physical form Opaque, off-white liquid

Technical data (typical properties)	Active content	%	100
	Moisture	%	~ 0.5
	Bulk density	lbs/gal	~ 7.4
	Dispersibility		Non- dispersible

Application

FoamStarST 2410 has the following advantages:

- Use 1/3 - 1/2 Less Defoamer
- Save at least 20 % on Defoamer Costs
- Non-separating & non-settling
- Extremely Effective in Low VOC coatings.
- Very Fast bubble-break versus conventional defoamers
- Effective against Micro-foam

Formulation guideline

In the grind portion of a flat paint formula, use 0.25 - 0.50 pounds of FoamStar ST 2410 per 100 gallons. In semi-gloss paint grind, use 0.50 - 1.0 pounds of FoamStar ST 2410 per 100 gallons. The rest of the FoamStar ST 2410 addition can be made to the letdown. FoamStar ST 2410 will be equally effective in both the letdown and the grind.

Storage

FoamStar ST 2410 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. FoamStar ST 2410 is shipped in 55gallon (200 liter) steel drums and plastic tote tanks. If subjected to below freezing temperatures, product may congeal or stratify. Warm to room temperature and mix well before using.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the FoamStar® ST 2410.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives